

## I.&lt;概要&gt;

本標準では、IP電話サービスの総合品質指標としてITU-T勧告G.107[1]に準拠したR値を用いることを前提として、この算出のためにサービス提供事業者が考慮すべき品質パラメータを特定し、その評価法を規定する。品質パラメータや評価法に関しては、該当するITU-T勧告に準拠することを基本とし、国際標準化との整合を図ることとする。

さらに、本標準では、ITU-T勧告G.107[1]が考慮していない品質要因がある点、R値と主観品質の対応関係に関する検証が必ずしも十分でない点を鑑み、R値を補完する品質パラメータ及びその評価方法も規定する。

## I.&lt;Overview&gt;

## The purpose of this standard

- taking account of the standardization trends of ITU-T and other organizations, to define a method of assessment with the overall quality index, the R value, specified in the ITU Recommendation G.107 as the overall quality index for IP telephony services and a method of assessment of parameters to complement the R value\*.

## TTC Study Policies

- In principle, make sure that the standard conforms to related international/regional standards (ITU-T, ETSI, and TIA standards).
- Use the overall quality index, the R value, for IP telephony services.
- Specify evaluation conditions and method of assessment for the calculation of the R value.
- In defining conditions and method of assessment, ensure the ease of assessment and fairness (strictness).

\* The R value is the index calculated based on the E-Model, which has been developed as a network planning tool. Because of the facts that there are quality factors that cannot be assessed with the R value and that the verification of the correspondence between the R value and subjective qualities has not been completed, parameters to complement the evaluation based on the R value are necessary, so is a method of their assessment.

## II.<参考>

### 1. 国際勧告等の関連

本標準に対応する国際標準は無い。

### 2. 参照文書

#### [1] ITU-T G.107 (03/2005)

The E-model, a computational model for use in transmission planning<sup>1</sup>

G.107 Erratum (07/2001)

Erratum to Recommendation ITU-T G.107 (07/2000).

JT-G.107 E-model 伝送計画のための計算モデル, 2003 年 4 月

Amendment 1: New Appendix II – Provisional impairment factor framework for wideband speech transmission (06/2006)

#### [2] ITU-T G.177 (09/1999)

Transmission planning for voiceband services over hybrid Internet/PSTN connections

#### [3] ETSI TR 101 329-1 (01/2002)

End-to-end Quality of Service in TIPHON systems; Part 1: General aspects of Quality of Service (QoS)

#### [4] ITU-T G.109 (09/1999)

Definition of categories of speech transmission quality

#### [5] ITU-T P.76 (11/1988)

Determination of loudness ratings; fundamental principles

JT-P76 ラウドネス定格の決定; 基本原理

#### [6] ITU-T P.79 (09/1999)

Calculation of loudness ratings for telephone sets

P.79 Erratum (05/2000)

Erratum to Recommendation ITU-T P.79 (09/1999).

JT-P79 電話セットのラウドネス値計算方法

#### [7] ITU-T G.711 (11/1988)

## II.<References>

### 1. Relation with international standards and national standards

This standard is TTC original.

### 2. References

#### [1] ITU-T G.107 (03/2005)

The E-model, a computational model for use in transmission planning<sup>1</sup>

G.107 Erratum (07/2001)

Erratum to Recommendation ITU-T G.107 (07/2000).

Amendment 1: New Appendix II – Provisional impairment factor framework for wideband speech transmission (06/2006)

#### [2] ITU-T G.177 (09/1999)

Transmission planning for voiceband services over hybrid Internet/PSTN connections

#### [3] ETSI TR 101 329-1 (01/2002)

End-to-end Quality of Service in TIPHON systems; Part 1: General aspects of Quality of Service (QoS)

#### [4] ITU-T G.109 (09/1999)

Definition of categories of speech transmission quality

#### [5] ITU-T P.76 (11/1988)

Determination of loudness ratings; fundamental principles

#### [6] ITU-T P.79 (09/1999)

Calculation of loudness ratings for telephone sets

P.79 Erratum (05/2000)

Erratum to Recommendation ITU-T P.79 (09/1999).

#### [7] ITU-T G.711 (11/1988)

Pulse code modulation (PCM) of voice frequencies G.711 Appendix I (09/1999) A high quality low-complexity algorithm for packet loss concealment with G.711	Pulse code modulation (PCM) of voice frequencies G.711 Appendix I (09/1999) A high quality low-complexity algorithm for packet loss concealment with G.711
JT-G711 音声周波数帯域信号の PCM 符号化方式	
[8] ITU-T G.113 (05/2002)	[8] ITU-T G.113 (05/2002)
Transmission impairments due to speech processing	Transmission impairments due to speech processing
JT-G.113 音声信号処理による伝送劣化, 2003 年 4 月	
[9] ITU-T P.833 (02/2001)	[9] ITU-T P.833 (02/2001)
Methodology for derivation of equipment impairment factors from subjective listening-only tests	Methodology for derivation of equipment impairment factors from subjective listening-only tests
JT-P833 受聴主観評価試験に基づいた装置劣化要因導出法	
[10] ITU-T P.834 (07/2002 (Pre-Published))	[10] ITU-T P.834 (07/2002 (Pre-Published))
A methodology for the derivation of equipment impairment factors from instrumental models	A methodology for the derivation of equipment impairment factors from instrumental models
JT-P834 計測モデルに基づく装置劣化要因導出法	
[11] ITU-T P.862 (02/2001 (Pre-Published))	[11] ITU-T P.862 (02/2001 (Pre-Published))
Perceptual evaluation of speech quality (PESQ), an objective method for end-to-end speech quality assessment of narrow-band telephone networks and speech codecs	Perceptual evaluation of speech quality (PESQ), an objective method for end-to-end speech quality assessment of narrow-band telephone networks and speech codecs
JT-P862 狹帯域電話網および符号化方式のエンド一エンド音声品質評価のための客観評価法	
[12] ETSI TS 101 329-5 (11/2000)	[12] ETSI TS 101 329-5 (11/2000)
End-to-end quality of service in TIPHON systems; Part5: Quality of service (QoS) measurement methodologies	End-to-end quality of service in TIPHON systems; Part5: Quality of service (QoS) measurement methodologies
[13] ETSI TR 101 329-7 (02/2002)	[13] ETSI TR 101 329-7 (02/2002)
End-to-end quality of service in TIPHON systems; Part7: Design guide for elements of TIPHON connection from an end-to-end speech transmission	End-to-end quality of service in TIPHON systems; Part7: Design guide for elements of TIPHON connection from an end-to-end speech transmission

performance point of view	performance point of view
[14] ITU-T G.122 (03/1993)	[14] ITU-T G.122 (03/1993)
Influence of national systems on stability and talker echo in international connections	Influence of national systems on stability and talker echo in international connections
[15] ITU-T G.131 (08/1996)	[15] ITU-T G.131 (08/1996)
Control of talker echo	Control of talker echo
[16] ITU-T G.165 (03/1993)	[16] ITU-T G.165 (03/1993)
Echo cancellers	Echo cancellers
JT-G.165 エコーキャンセラ, 2003 年 4 月	
[17] ITU-T G.168 (04/2000)	[17] ITU-T G.168 (04/2000)
Digital network echo cancellers	Digital network echo cancellers
[18] ITU-T P.310 (05/2000)	[18] ITU-T P.310 (05/2000)
Transmission characteristics for telephone-band (300–3400 Hz) digital telephones	Transmission characteristics for telephone-band (300–3400 Hz) digital telephones
[19] ETSI TR 101 329-6 (02/2002)	[19] ETSI TR 101 329-6 (02/2002)
End-to-end Quality of Service in TIPHON systems; Part 6: Actual measurements of network and terminal characteristics and performance parameters in TIPHON networks and their influence on voice quality	End-to-end Quality of Service in TIPHON systems; Part 6: Actual measurements of network and terminal characteristics and performance parameters in TIPHON networks and their influence on voice quality
[20] ETSI TS 101 329-2 (01/2002)	[20] ETSI TS 101 329-2 (01/2002)
End-to-end quality of service in TIPHON systems; Part2: Definition of speech Quality of Service (QoS) classes	End-to-end quality of service in TIPHON systems; Part2: Definition of speech Quality of Service (QoS) classes
[21] ITU-T E.500 (11/1998)	[21] ITU-T E.500 (11/1998)
Traffic intensity measurement principles	Traffic intensity measurement principles
[22] ETSI EG 201 769 (10/2000)	[22] ETSI EG 201 769 (10/2000)
QoS parameter definitions and measurements; Parameters for voice telephony service required under the ONP voice telephony directive	QoS parameter definitions and measurements; Parameters for voice telephony service required under the ONP voice telephony directive
[23] ITU-T Y.1541 (05/2002 (Pre-Published))	[23] ITU-T Y.1541 (05/2002 (Pre-Published))
Network performance objectives for IP-Based services	Network performance objectives for IP-Based services

[24] ITU-T P.800 (08/1996)

Methods for subjective determination of transmission quality

JT-P800 伝送品質の主観的決定法

[25] ITU-T G.114 (05/2000)

One-way transmission time

[26] ANSI/IEEE Std 802.11, 1999 Edition

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

[27] IEEE Std 802.11b-1999 (Supplement to ANSI/IEEE Std 802.11, 1999 Edition)

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

Higher-Speed Physical Layer Extension in the 2.4 GHz Band

[28] IEEE Std 802.11a-1999 (Supplement to IEEE Std 802.11-1999)

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

High-speed Physical Layer in the 5 GHz Band

[29] IEEE Std 802.11g™-2003 [Amendment to IEEE Std 802.11™, 1999 Edition (Reaff 2003) as amended by IEEE Stds 802.11a™-1999, 802.11b™-1999, 802.11b™-1999/Cor 1-2001, and 802.11d™-2001]

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

Amendment 4: Further Higher Data Rate Extension in the 2.4 GHz Band

[30] ARIB STD-T71 2.0 版(06/2003)

Broadband Mobile Access Communication System (CSMA)

広帯域移動アクセスシステム(CSMA)

[31] ITU-T P.862.1 (11/2003)

Mapping function for transforming P.862 raw result scores to MOS-LQO

[32] ITU-T P.862.3 (11/2005)

Application guide for objective quality measurement based on Recommendations P.862, P.862.1 and P. 862.2

[33] ITU-T P.830 (02/1996)

Subjective performance assessment of telephone-band and wideband digital codecs

[34] ITU-T Recommendation P.862.2 (11/2005)

Wideband extension to Recommendation P.862 for the assessment of wideband telephone networks and speech codecs

[24] ITU-T P.800 (08/1996)

Methods for subjective determination of transmission quality

[25] ITU-T G.114 (05/2000)

One-way transmission time

[26] ANSI/IEEE Std 802.11, 1999 Edition

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

[27] IEEE Std 802.11b-1999 (Supplement to ANSI/IEEE Std 802.11, 1999 Edition)

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

Higher-Speed Physical Layer Extension in the 2.4 GHz Band

[28] IEEE Std 802.11a-1999 (Supplement to IEEE Std 802.11-1999)

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

High-speed Physical Layer in the 5 GHz Band

[29] IEEE Std 802.11g™-2003 [Amendment to IEEE Std 802.11™, 1999 Edition (Reaff 2003) as amended by IEEE Stds 802.11a™-1999, 802.11b™-1999, 802.11b™-1999/Cor 1-2001, and 802.11d™-2001]

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

Amendment 4: Further Higher Data Rate Extension in the 2.4 GHz Band

[30] ARIB STD-T71 2.0 版(06/2003)

Broadband Mobile Access Communication System (CSMA)

[31] ITU-T P.862.1 (11/2003)

Mapping function for transforming P.862 raw result scores to MOS-LQO

[32] ITU-T P.862.3 (11/2005)

Application guide for objective quality measurement based on Recommendations P.862, P.862.1 and P. 862.2

[33] ITU-T P.830 (02/1996)

Subjective performance assessment of telephone-band and wideband digital codecs

[34] ITU-T Recommendation P.862.2 (11/2005)

Wideband extension to Recommendation P.862 for the assessment of wideband telephone networks and speech codecs

- [35] ITU-T Recommendation P.564 (7/2006)  
Conformance testing for narrowband voice over IP transmission quality assessment models
- [36] IETF RFC3611 (11/2003)  
RTP Control Protocol Extended Reports (RTCP XR)
- [37] ITU-T Y.1540 (12/2002)  
Internet protocol data communication service - IP packet transfer and availability performance parameters  
JT-Y1540 インターネットプロトコルデータ通信サービス -IPパケット転送性能/パラメータと可用性パラメータ, 2001年11月
- [38]ITU-T P.1010 (07/2004)  
Fundamental voice transmission objectives for VoIP terminals and gateways
- [39]ITU-T P.863 (01/2011)  
Perceptual Objective Listening Quality Assessment An advanced objective perceptual method for end-to-end listening speech quality evaluation of fixed, mobile, and IP-based networks and speech codecs covering narrowband, wideband, and super-wideband signals
- [40]ITU-T SG 12 P.Imp863 (11/2011)  
Implementer's Guide I for ITU-T P.863: Mapping function of P.863 results into MOS-LQO
- [41]ITU-T P.863.1 (05/2013)  
Application Guide for Recommendation ITU-T P.863

### 3. 改版の履歴

版数	制定日	改版内容
第1版	2003年4月23日	制定
第2版	2005年6月2日	・パケット長とコーデックのパケット損失耐性の適用範囲の拡充・無線LANを用いたIP電話の通話品質評価に関する留意事項の追加(TS-1010仕様の盛り込み)・ソフトフォンを用いたIP電話の通話品質評価に関する留意事項の追加・相互接続環境におけるIP電話の通話品質評価に関する留意事項の追加

- [35] ITU-T Recommendation P.564 (7/2006)  
Conformance testing for narrowband voice over IP transmission quality assessment models
- [36] IETF RFC3611 (11/2003)  
RTP Control Protocol Extended Reports (RTCP XR)
- [37] ITU-T Y.1540 (12/2002)  
Internet protocol data communication service - IP packet transfer and availability performance parameters
- [38]ITU-T P.1010 (07/2004)  
Fundamental voice transmission objectives for VoIP terminals and gateways
- [39]ITU-T P.863 (01/2011)  
Perceptual Objective Listening Quality Assessment An advanced objective perceptual method for end-to-end listening speech quality evaluation of fixed, mobile, and IP-based networks and speech codecs covering narrowband, wideband, and super-wideband signals
- [40]ITU-T SG 12 P.Imp863 (11/2011)  
Implementer's Guide I for ITU-T P.863: Mapping function of P.863 results into MOS-LQO
- [41]ITU-T P.863.1 (05/2013)  
Application Guide for Recommendation ITU-T P.863

### 3. Change history

Version	Date	Outline
1	April 4, 2003	Published

第3版	2006 年 6 月 1 日	<ul style="list-style-type: none"> <li>• PESQ アプリケーションガイド (ITU-T 勧告 P.862.3)に対応したガイダンスの追加</li> <li>• ITU-T 勧告 G.107 改版に伴う記述の修正</li> </ul>
第4版	2007 年 3 月 15 日	<ul style="list-style-type: none"> <li>• 付録 IX 広帯域IP電話サービスの通話品質評価法の追記</li> </ul>
第5版	2008 年 8 月 25 日	<ul style="list-style-type: none"> <li>• インサービス品質管理に関する記述追加</li> <li>• IP 電話の通話品質評価における NW 品質値の扱いに関する留意事項の追加</li> </ul>
第6版	2012 年 8 月 30 日	<ul style="list-style-type: none"> <li>• POLQA に関する記述追加</li> <li>• 広帯域IP電話サービスの通話品質評価法に関する記述の削除</li> </ul>
第7版	2013 年 11 月 14 日	<ul style="list-style-type: none"> <li>• POLQA アプリケーションガイド (ITU-T 勧告 P.863.1)に関する記述追加</li> </ul>
第8版	2015 年 5 月 21 日	<ul style="list-style-type: none"> <li>• OAB-J IP 電話の品質要件の見直しに対応して測定条件を統一したガイドライン文書に関する記述の追加 (「IP 電話の通話品質測定ガイドライン (TR-1054)」の参照)</li> <li>• 6.3 節の標準系、限界系の記述を TR-1054 と整合するよう修正</li> </ul>
第8.1版	2015 年 9 月 9 日	誤記 (図の欠損)などを修正
第9版	2018 年 8 月 29 日	<ul style="list-style-type: none"> <li>• 4.2 節の接続パターンに関する記述追加</li> <li>• 上記に関連する用語の追加</li> </ul>

2	June 2, 2005	<ul style="list-style-type: none"> <li>• Addition of a condition and enhancement of notices</li> <li>• Based on feedback from domestic IP telephony service experience.</li> <li>• Changes from JJ-201.01 (Apr. 2003)</li> <li>1.Addition of the Condition about Packet Length and Packet Loss of CODEC</li> <li>2.Notice on Speech Quality Assessment of IP Telephony over Wireless LAN</li> <li>3.Notice on Speech Quality Assessment of IP Telephony that uses Softphone</li> <li>4.Notice on Speech Quality Assessment of IP Telephony on interoperability between IP Networks</li> </ul>
3	June 1, 2006	<ul style="list-style-type: none"> <li>• Addition of the guidance of ITU-T Rec. P.862.3 Application Guide.</li> <li>• Modify the description of ITU-T Rec G.107 revision.</li> </ul>
4	March 15, 2007	<ul style="list-style-type: none"> <li>• Addition of the Appendix IX “A Method for Speech Quality Assessment of Wideband IP Telephony”</li> </ul>
5	Aug. 25, 2008	<ul style="list-style-type: none"> <li>• Addition of the description for in-service quality management.</li> <li>• Addition of the guideline for IP network performance measurement in quality assessment of IP Telephony</li> </ul>

6	Aug 30, 2012	<ul style="list-style-type: none"> <li>▪ Addition of the description of ITU-T Rec. P.863 “POLQA.”</li> <li>▪ Deletion of the description of a method for speech quality assessment of wideband IP telephony.</li> </ul>
7	Nov 14, 2013	<ul style="list-style-type: none"> <li>▪ Addition of the description of ITU-T Rec. P.863.1 “Application Guide for Recommendation ITU-T P.863.”</li> </ul>
8	May 21, 2015	<ul style="list-style-type: none"> <li>▪ Addition of the description of TR-1054 “A Speech Quality Measurement Guideline for IP Telephony”</li> <li>▪ Modify the description of clause 6.3 ()</li> </ul>
8.1	Sep 09.2015	<ul style="list-style-type: none"> <li>▪ Error(Loss of figure etc) correction</li> </ul>
9	Aug 29,2018	<ul style="list-style-type: none"> <li>▪ Addition of the description of Connection pattern in clause 4.2.</li> <li>▪ Addition of some terminology.</li> </ul>

#### 4. 標準策定部門

網管理専門委員会

4. Working Group that developed this standard

Network Management Working Group

#### III.<目次>

##### <参考>

1. 用語と定義
2. 関連する勧告・規定など
3. 規定範囲
4. 対象ネットワークと前提条件
  - 4.1 レファレンス接続系
  - 4.2 接続パターン

#### III.<Table of contents>

##### <Reference>

1. Terminology and definition
2. Reference standard and specifications etc.
3. Scope
4. Target network and condition
  - 4.1 Reference network segment
  - 4.2 Connection pattern

5. E-model 概要
6. R 値の評価方法
- 6.1 R 値パラメータの分類と要規定項目
- 6.2 各パラメータの評価方法
- 6.2.1 音質パラメータ(qdu, Ie, Bpl, Ppl)
- 6.2.2 エコー評価法(TELR)
- 6.2.3 遅延評価法(T, Ta, Tr)
- 6.3 パラメータの測定条件
- 6.3.1 測定日、測定時間帯
- 6.3.2 測定サンプル時間
- 6.3.3 測定期間
7. R 値の解釈ガイドライン
8. R 値を補完するパラメータとその評価方法
- 8.1 遅延
- 8.2 エコー
- 8.3 音質
- 8.3.1 評価方法
- 8.3.2 R 値に対応した所要受聴 MOS 値
9. インサービス品質管理
- 9.1 ダイナミックオペレーションモード(モード A)
- 9.2 スタティックオペレーションモード(モード B)
- 付録 I 欧米と日本の MOS 値の違い
- 付録 II エコーリターンロスの測定法
- 付録 III パケット長とコーデックのパケット損失耐性の関係
- 付録 IV POLQA 及び PESQ の概要とアプリケーションガイドの要点
- 付録 V レファレンス条件を基準にした評価値の変換
- 付録 VI 無線 LAN を用いた IP 電話の通話品質評価に関する留意事項
5. E-model outline
6. R value evaluation
- 6.1 Classification of R parameters and items required definition
- 6.2 Evaluation method of each parameter
- 6.2.1 Acoustic parameter(qdu, Ie, Bpl, Ppl)
- 6.2.2 Echo evaluation method(TELR)
- 6.2.3 Delay evaluation method(T, Ta, Tr)
- 6.3 Monitoring condition of paremeters
- 6.3.1 Monitoring day, monitoring time zone
- 6.3.2 Monitoring sample time
- 6.3.3 Monitoring period
7. Interpretation guideline of R value
8. Supplement parameters of R value and evaluation method
- 8.1 Delay
- 8.2 Echo
- 8.3 Acoustics
- 8.3.1 Evaluation method
- 8.3.2 Required hearing MOS value for R value
9. In-service quality management
- 9.1 Dynamic Operation Mode (Mode A)
- 9.2 Static Operation Mode (Mode B)
- Appendix I The difference between Japanese MOS and Euramerican MOS
- Appendix II Monitoring method of echo return loss
- Appendix III Relation of packet length and codec packet loss resistance
- Appendix IV Outline of POLQA and PESQ, and their Application Guides
- Appendix V Conversion of the evaluated value based on reference condition
- Appendix VI Notice on Speech Quality Assessment of IP Telephony over Wireless LAN

付録VII ソフトフォンを用いたIP電話の通話品質評価に関する留意事項

AppendixVII Notice on Speech Quality Assessment of IP Telephony used Software-Phone

付録VIII 相互接続環境における通話品質評価に関する留意事項

AppendixVIII Notice on Speech Quality Assessment of IP Telephony between IP Networks

付録IX IP電話の通話品質評価におけるNW品質値の扱いに関する留意事項

Appendix IX Guideline for IP Network Performance Measurements in Quality Assessment of IP Telephony

付録X 参照端末を想定したIP電話の通話品質の評価例

Appendix X The Example of Evaluation of IP Telephony Supposing the Reference Terminal

参考文献

Bibliography