

# **JT-Q2971    Broadband Integrated Services Digital Network (B-ISDN) Digital Subscriber Signalling System No. 2 (DSS 2) User Network Interface Layer 3 Specification for Point-To- Multipoint Call/Connection Control**

## **1. Relation with the international standards**

This standard is based on the ITU-T Recommendation Q.2971 which was approved in the ITU-T SG11 meeting (May 1995, Geneva) and Corrigendum 1 to Recommendation Q.2971 which was agreed in the ITU-T SG11 meeting (November 1999, Geneva).

## **2. Difference from ITU-T Recommendations / international standards**

### **2.1 Selected option items**

None.

### **2.2 Selected national option items**

None.

### **2.3 Others**

(1) This standard does not specify followings comparing with the ITU-T Recommendation Q.2971.

- (a) Annex C: Amendments to Recommendation Q.2951 to support calls/connections using the procedures of Recommendation Q.2971
- (b) Annex D: Amendments to Recommendation Q.2957 to support calls/connections using the procedures of Recommendation Q.2971

The reason is that the TTC standards corresponding to the ITU-T Recommendations Q.2951 and Q.2957 were not established at the time of first edition establishment.

## **3. History of revised versions**

Version	Date	Outline
1	April 24, 1996	Published
2	April 19, 2001	It revised in order to include the contents of the Corrigendum 1 to Recommendation Q.2971 which was agreed in the ITU-T SG11 meeting (November 1999).

## **4. Remarks**

None.