

**1. Relations with international standards**

"User-to-User Signalling (UUS)" conforms to the draft text for Recommendation Q.737.1 studied at the ITU-T SG 11 editing meeting in November 1991.

**2. Summary of departures from ITU-T Recommendations**

**2.1 Optional items**

None

**2.2 National items**

None

**2.3 Others**

- (1) This standard has no items that differ from the ITU-T Recommendation.
- (2) The following items are deleted from the above ITU-T Recommendation:
  - (a) description for international gateway exchanges
  - (b) User-to-User Signalling, Service 2 and Service 3

They have been deleted for the following reasons:

- (a) is deleted because it is defined for international connection.
  - (b) is deleted because it is premature in ITU-T.
- (3) "User-to-User Signalling (UUS), service 1" specified in JT-Q730 (Version 2, established at April 26, 1991) is revised in order to conform to the current chapter composition in ITU-T Recommendation. The following table shows the additional specifications with this revision.

Table 1 Additional specifications with this revision

Supplementary services	Number	Additional specifications
User-to-User Signalling(UUS)	[I-1]	Clarification of usage of User-to-user information Parameter in the case of requiring explicitly.procedure in the case of discarding User-to-user information Parameter.

**2.4 Comparison of chapter composition between the ITU-T Recommendation and this standard.**

ITU-T Rec.	Standards	Supplementary services
Q.731.1 Section 1	[I-1]	User-to-User Signalling (UUS), service 1

**3. The history of revised versions**

Versions	Date	Outline
1	April 28,1992	Established

#### 4. Others

None