

TS-M2M-0006v1.0.1

oneM2M 技術仕様書
BBF 仕様によるデバイス管理

oneM2M Technical Specification
Management Enablement (BBF)

2015 年 3 月 16 日制定

一般社団法人
情報通信技術委員会

THE TELECOMMUNICATION TECHNOLOGY COMMITTEE

本書は、一般社団法人情報通信技術委員会が著作権を保有しています。
内容の一部または全部を一般社団法人情報通信技術委員会の許諾を得ることなく複製、
転載、改変、転用及びネットワーク上での送信、配布を行うことを禁止します。

oneM2M 技術仕様書－BBF 仕様によるデバイス管理 [oneM2M Technical Specification - Management Enablement (BBF)]

＜参考＞ [Remarks]

1. 英文記述の適用レベル [Application level of English description]

適用レベル [Application level] : E2

本標準の本文、付属資料および付録の文章および図に英文記述を含んでいる。

[English description is included in the text and figures of main body, annexes and appendices.]

2. 国際勧告等の関連 [Relationship with international recommendations and standards]

本標準は、oneM2M で承認された Technical Specification 0006V1.0.1 に準拠している。

[This standard is standardized based on the Technical Specification 0006V1.0.1 approved by oneM2M.]

3. 上記国際勧告等に対する追加項目等 [Departures from international recommendations]

原標準に対する変更項目 [Changes to original standard]

原標準が参照する標準のうち、TTC 標準に置き換える項目。[Standards referred to in the original standard, which are replaced by TTC standards.]

原標準が参照する標準のうち、それらに準拠した TTC 標準等が制定されている場合は自動的に最新版 TTC 標準等に置き換え参照するものとする。 [Standards referred to in the original standard should be replaced by derived TTC standards.]

4. 工業所有権 [IPR]

本標準に関わる「工業所有権等の実施の権利に係る確認書」の提出状況は、T T C ホームページによる。

[Status of “Confirmation of IPR Licensing Condition” submitted is provided in the TTC web site.]

5. 作成専門委員会 [Working Group]

oneM2M 専門委員会 [oneM2M Working Group]



oneM2M TECHNICAL SPECIFICATION

Document Number	TS-0006-V1.0.1
Document Name:	Management enablement (BBF)
Date:	2015-January-30
Abstract:	<p>Specifies the usage of the BBF TR-069 protocol and the corresponding message flows including normal cases as well as error cases to fulfil the oneM2M management requirements.</p> <ul style="list-style-type: none">• Protocol mapping between the oneM2M service layer and BBF TR-069 protocol. The Mca reference point, ms interface and la interface are possibly involved in this protocol mapping.• Mapping between the oneM2M management related resources and the TR-069 protocol RPCs and TR-181i2 data model.• Specification of new TR-181 data model elements to fulfil oneM2M specific management requirements that cannot be currently translated.

This Specification is provided for future development work within oneM2M only. The Partners accept no liability for any use of this Specification.

The present document has not been subject to any approval process by the oneM2M Partners Type 1. Published oneM2M specifications and reports for implementation should be obtained via the oneM2M Partners' Publications Offices.

About oneM2M

The purpose and goal of oneM2M is to develop technical specifications which address the need for a common M2M Service Layer that can be readily embedded within various hardware and software, and relied upon to connect the myriad of devices in the field with M2M application servers worldwide.

More information about oneM2M may be found at: <http://www.oneM2M.org>

Copyright Notification

No part of this document may be reproduced, in an electronic retrieval system or otherwise, except as authorized by written permission.

The copyright and the foregoing restriction extend to reproduction in all media.

© 2015, oneM2M Partners Type 1 (ARIB, ATIS, CCSA, ETSI, TTA, TTC).

All rights reserved.

Notice of Disclaimer & Limitation of Liability

The information provided in this document is directed solely to professionals who have the appropriate degree of experience to understand and interpret its contents in accordance with generally accepted engineering or other professional standards and applicable regulations. No recommendation as to products or vendors is made or should be implied.

NO REPRESENTATION OR WARRANTY IS MADE THAT THE INFORMATION IS TECHNICALLY ACCURATE OR SUFFICIENT OR CONFORMS TO ANY STATUTE, GOVERNMENTAL RULE OR REGULATION, AND FURTHER, NO REPRESENTATION OR WARRANTY IS MADE OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. NO oneM2M PARTNER TYPE 1 SHALL BE LIABLE, BEYOND THE AMOUNT OF ANY SUM RECEIVED IN PAYMENT BY THAT PARTNER FOR THIS DOCUMENT, WITH RESPECT TO ANY CLAIM, AND IN NO EVENT SHALL oneM2M BE LIABLE FOR LOST PROFITS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. oneM2M EXPRESSLY ADVISES ANY AND ALL USE OF OR RELIANCE UPON THIS INFORMATION PROVIDED IN THIS DOCUMENT IS AT THE RISK OF THE USER.

Contents

49	Contents	3
50	1. Scope.....	5
51	2 References	5
52	2.1 Normative references	5
53	2.2 Informative references.....	5
54	3 Definitions, symbols, abbreviations and acronyms	5
55	3.1 Definitions	5
56	3.2 Abbreviations.....	5
57	3.4 Acronyms	6
58	4 Conventions.....	6
59	5 Mapping of basic data types	6
60	6 Mapping of identifiers.....	6
61	6.1 Mapping of Device identifiers to the Node Resource.....	7
62	6.2 Identifier of an object instance.....	7
63	7 Mapping of resources.....	7
64	7.1 General mapping assumptions	8
65	7.1.1 Mapping of Device identifiers.....	8
66	7.1.2 Mapping of Embedded Devices.....	8
67	7.2 Resource [deviceInfo]	8
68	7.3 Resource [memory]	9
69	7.4 Resource [battery]	9
70	7.5 Resource [areaNwkInfo]	10
71	7.6 Resource [areaNwkDeviceInfo].....	10
72	7.7 Resource [eventLog]	11
73	7.8 Resource [deviceCapability].....	11
74	7.9 Resource [firmware].....	12
75	7.10 Resource [software]	13
76	7.11 Resource [reboot].....	15
77	7.12 Resource [cmdhPolicy]	15
78	7.12.1 Resource [activeCmdhPolicy]	16
79	7.12.2 Resource [cmdhDefaults].....	16
80	7.12.3 Resource [cmdhDefEcValues]	17
81	7.12.4 Resource [cmdhEcDefParamValues].....	17
82	7.12.5 Resource [cmdhLimits].....	18
83	7.12.6 Resource [cmdhNetworkAccessRules]	18
84	7.12.7 Resource [cmdhNwAccessRule]	19
85	7.12.8 Resource [cmdhBuffer].....	19
86	7.13 Resource Type <mgmtCmd>.....	20
87	7.14 Resource Type <execInstance>	20
88	8 Mapping of procedures for management.....	21
89	8.1 Resource Type <mgmtObj> primitive mappings.....	21
90	8.1.1 Alias-Based Addressing Mechanism.....	21
91	8.1.2 Create primitive mapping.....	21
92	8.1.2.1 M2M Service Layer Resource Instance Identifier mapping.....	21
93	8.1.3 Delete primitive mapping.....	22
94	8.1.3.1 Delete primitive mapping for deletion of Object Instances.....	22
95	8.1.3.2 Delete primitive mapping for software un-install operation	22
96	8.1.4 Update primitive mapping.....	24
97	8.1.4.1 Update primitive mapping for Parameter modifications.....	24
98	8.1.4.2 Update primitive mapping for upload file transfer operations	24
99	8.1.4.3 Update primitive mapping for download file transfer operations.....	26
100	8.1.4.4 Update primitive mapping for reboot operation	27

101	8.1.4.5	Update primitive mapping for factory reset operation	28
102	8.1.4.6	Update primitive mapping for software install operation	28
103	8.1.5	Retrieve primitive mapping.....	30
104	8.1.6	Notify primitive mapping.....	30
105	8.1.6.1	Procedure for subscribed Resource attributes.	30
106	8.1.6.2	Notification primitive mapping.....	31
107	8.2	<mgmtCmd> and <execInstance> resource primitive mappings	32
108	8.2.1	Update (Execute) primitive for the <mgmtCmd> resource	32
109	8.2.1.1	Execute File Download.....	32
110	8.2.1.2	Execute File Upload Operations.....	33
111	8.2.1.3	Report Results using TransferComplete RPC	34
112	8.2.1.4	Execute Software Operations with ChangeDUState RPC.....	35
113	8.2.1.5	Report Results with ChangeDUStateComplete RPC.....	35
114	8.2.1.6	Execute Reboot operation	37
115	8.2.1.7	Execute Factory Reset operation.....	37
116	8.2.2	Delete <mgmtCmd> resource primitive mapping.....	38
117	8.2.3	Update (Cancel) <execInstance> primitive mapping.....	38
118	8.2.4	Delete <execInstance> primitive mapping.....	39
119	9	Server Interactions	40
120	9.1	Communication Session Establishment.....	40
121	9.1.1	IN-CSE to ACS Communication Session Establishment	40
122	9.1.2	ACS to IN-CSE Communication Session Establishment	40
123	9.2.3	ACS and IN-CSE Communication Session Requirements.....	40
124	9.2	Processing of Requests and Responses.....	41
125	9.2.1	Request and Notification Formatting	41
126	9.2.2	ACS Request Processing Requirements.....	41
127	9.2.3	ACS Notification Processing Requirements.....	41
128	9.3	Discovery and Synchronization of Resources.....	41
129	9.4	Access Management.....	41
130	9.4.1	Access Management Requirements.....	42
131	10	New Management Technology Specific Resources.....	42
132	History		42

134

135
136
137

138

139

140
141

142
143
144
145
146
147
148
149

150
151
152
153

154

155

156
157
158

159

160

161
162
163
164
165
166
167
168
169

1. Scope

The present document describes the protocol mappings between the management Resources for oneM2M and the BBF TR-181i2 Data Model [6].

2 References

2.1 Normative references

The following referenced documents are necessary, partially or totally, for the application of the present document. Their use in the context of this TS is specified by the normative statements that are referring back to this clause.

[1]	oneM2M TS-0001: “Functional Architecture”.
[2]	oneM2M TS-0004: “Service Layer Core Protocol Specification”.
[3]	oneM2M TS-0011: “Definitions and Acronyms”.
[4]	BBF: “TR-069 CPE WAN Management Protocol” Issue: 1 Amendment 5, November 2013.
[5]	BBF: “TR-106 Data Model Template for TR-069-Enabled Devices”, Issue 1, Amendment 7, September 2013.
[6]	BBF: “TR-181 Device Data Model for TR-069, Issue 2 Amendment 8”, September 2014.
[7]	BBF: “TR-131 ACS Northbound Interface Requirements, Issue:1”, November 2009.

2.2 Informative references

[i.1]	oneM2M Drafting Rules (http://member.onem2m.org/Static_pages/Others/Rules_Pages/oneM2M-Drafting-Rules-V1_0.doc)
-------	--

3 Definitions, symbols, abbreviations and acronyms

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TS-0011 [3] apply.

CPE Proxier	A CPE that is capable of proxying the communication between an ACS and a Proxied Device as defined in TR-069 [4].
-------------	---

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TS-0011 [3] apply.

ACS	Auto-Configuration Server
ADN	Application Dedicated Node
AE	Application Entity
ASN	Application Service Node
CMDH	Communication Management and Delivery Handling
CPE	Customer Premise Equipment
CSE	Common Services Entity
CWMP	CPE WAN Management Protocol
DU	Deployment Unit

IN-CSE	CSE which resides in the Infrastructure Node
LAN	Local Area Network
MN	Middle Node
OUI	Organizationally Unique Identifier
PC	Product Class
RPC	Remote Procedure Call
SN	Serial Number
URI	Uniform Resource Identifier
URL	Uniform Resource Locator
USB	Universal Serial Bus
UUID	Universal Unique Identifier
XML	Extensible Markup Language

3.4 Acronyms

For the purposes of the present document, the acronyms given in TR-0004 [3] apply.

4 Conventions

The key words “Shall”, ”Shall not”, “May”, ”Need not”, “Should”, ”Should not” in this document are to be interpreted as described in the oneM2M Drafting Rules [i.1]

5 Mapping of basic data types

TR-106 [5] specifies the object structure supported by TR-069 enabled devices and specifies the structural requirements for the data hierarchy. This clause includes the mapping attribute data types to TR-181 [6] parameters which follows the conventions of section 3 of TR-106 [5] and data types described in Table 4 of TR-106 [5].

Table 5-1: Data Type Mapping

oneM2M Data Types	Mapping to data types in TR-106	Conversion Notes
xs:boolean	boolean	
xs:string	string	Mapping is constrained to the size of the string
xs:unsignedInt	unsignedInt	
xs:unsignedLong	unsignedLong	
xs:integer	long	Mapping is constrained to the size of the long data type.
Xs:positiveInteger	unsignedLong	Mapping is constrained to a lower limit of 1 and the size of the unsignedLong data type.
Xs:nonNegativeInteger	unsignedLong	Mapping is constrained the size of the unsignedLong data type.
Comma separated Lists	Comma separated Lists	Data structure is represented by comma separated list as described in section 3.2.3 of TR-106 [5].

In some instances the conversion of the contents between data types will cause an error to occur (e.g., xs:integer to long). When an error occurs in the conversion of a data type, the STATUS_BAD_REQUEST response status code.

6 Mapping of identifiers

The TR-069 [4] specification defines three (3) types of devices, known as CPEs, that are capable of being managed from the perspective of the TR-069 agent:

- CPE that hosts the TR-069 agent: Section A.3.3.1 Inform of TR-069 [4] defines the required fields for a CPE to be identified. These fields include the OUI and Serial Number of the CPE assigned by the CPE manufacturer. Optionally the manufacturer may assign a Product Class to the CPE. The format of the identifier is as follows: OUI-[PC]-JSN.

- Virtual Device: This type of device is addressed as a CPE. The Virtual Device has its own OUI-[PC-]SN as represented by the CPE Proxier. The CPE Proxier emulates a CWMP agent for each Virtual Device.
- Embedded Device: This type of device is addressed as one or more objects within the data model of the CPE that hosts the TR-069 agent.

6.1 Mapping of Device identifiers to the Node Resource

Node Resources are identified for each instance of an ADN, ASN and MN node and are identified using the M2M Node Identifier (M2M-Node-ID) defined in the oneM2M Functional Architecture [1].

CPE Device identifiers shall map to the nodeID attribute of the <node> resource. The CPE Device identifiers are obtained from the contents of the following attributes:

- Device.DeviceInfo.ManufacturerOUI
- Device.DeviceInfo.ProductClass
- Device.DeviceInfo.SerialNumber

Virtual Device identifiers shall map to the nodeID attribute of the <node> resource. The Virtual Device identifiers are obtained from the CPE Proxier using the contents of the attributes:

- Device.ManagementServer.VirtualDevice.{i}.ManufacturerOUI
- Device.ManagementServer.VirtualDevice.{i}.ProductClass
- Device.ManagementServer.VirtualDevice.{i}.SerialNumber

Embedded Device identifiers shall map to the nodeID attribute of the <node> resource. The Embedded Device identifiers are obtained using the containing CPE Device or Virtual Device identifiers along with the contents of the attributes of the:

- Device.ManagementServer.EmbeddedDevice.{i}.ControllerID
- Device.ManagementServer.EmbeddedDevice.{i}.ProxiedDeviceID

6.2 Identifier of an object instance

The TR-069 [4] specification permits objects to have multiple object instances where each object instance is contained within the objectPath attribute of the Resource within the context of the Resource's objectId as defined in clause 7.1.

In order to allow the AE or CSE that originated the request that manipulates a Resource to easily align the M2M Service Layer with the Resource's external technology identifier, the value of the object instance "{i}" should be a part of the identifier of the Resource in the M2M Service Layer where possible. For example if the [areaNetwork] resource has an object instance identifier of "Device.X_oneM2M_org_CSE.1.M2MareaNetworkDevice.[foo]" then the M2M Service Layer Resource should be identified using the object instance of the underlying technology (e.g., "/foo" for the Resource areaNetwork).

7 Mapping of resources

This clause contains all information on how to map management resources from TS-0004 [2] to managed objects and parameters as defined in the TR-181 [6] data model or the Remote Procedure Calls (RPCs) in TR-069 [4].

7.1 General mapping assumptions

TR-069 [4] specifies a protocol for communication between a CPE (Customer Premises Equipment) and an ACS (Auto-Configuration Server). Any TR-069 enabled device has to follow the data model as described in the TR-106 [5] and TR-181 [6] as well as RPCs described in TR-069 [4].

As TR-181 [6] is the model that the Resources are mapped, all Resources shall have the URI of the TR-181[6] namespace (e.g., “urn:broadband-forum-org:tr-181-2-7-0”).

7.1.1 Mapping of Device identifiers

The Device identifiers for CPEs are mapped to the Resource Type [deviceInfo].

For CPE and Virtual Devices map their Device Identifiers (OUI-[PC-]SN) to the manufacturer, deviceType and deviceLabel attributes of the Resource [deviceInfo].

For Embedded Devices, the ControllerID and ProxiedDeviceID parameters of the Device.ManagementServer.EmbeddedDevice.{i} object instance are mapped to the deviceLabel attribute of the Resource [deviceInfo] as a comma separated list: “Device.ManagementServer.EmbeddedDevice.{i}.ControllerID, Device.ManagementServer.EmbeddedDevice.{i}.ProxiedDeviceID”.

7.1.2 Mapping of Embedded Devices

The TR-181 [6] specification does not provide a mechanism where Embedded Devices provide information related to the Device.DeviceInfo objects and sub-objects. Instead the TR-181 [6] provides this information in a manner that is reliant on the Embedded Device’s underlying technology (e.g., ZigBee®, UpnP).

As such the mapping of the [memory] and [battery] Resources are implementation specific for each underlying technology and is outside the scope of this specification.

7.2 Resource [deviceInfo]

The Resource [deviceInfo] is a read-only Resource that shall map to the Device.DeviceInfo object of TR-181 [6] for CPE and Virtual Devices.

The information shall be retrieved using the GetParameterValues RPC of TR-069 [4].

Note: The SerialNumber, ModelNumber, ProductClass attributes for a Virtual device are the same values as the Device.ManagementServer.VirtualDevice.{i} object in the CPE Proxier.

Table 7.2-1: Resource [deviceInfo] for CPE and Virtual Devices

Attribute Name of [deviceInfo]	TR-181 Parameter
deviceLabel	Device.DeviceInfo.SerialNumber
manufacturer	Device.DeviceInfo.Manufacturer
model	Device.DeviceInfo.ModelNumber
deviceType	Device.DeviceInfo.ProductClass
fwVersion	Device.DeviceInfo.SoftwareVersion if the device supports only 1 software version. If the device support multiple software versions this shall map to Device.DeviceInfo.AdditionalSoftwareVersion
swVersion	Device.DeviceInfo.SoftwareVersion
hwVersion	Device.DeviceInfo.HardwareVersion

267

Table 7.2-2: Resource [deviceInfo] for Embedded Devices

Attribute Name of [deviceInfo]	TR-181 Parameter
deviceLabel	Comma separated list: “Device.ManagementServer.EmbeddedDevice.{i}.ControllerID, Device.ManagementServer.EmbeddedDevice.{i}.ProxiedDeviceID
manufacturer	No mapping available
model	No mapping available
deviceType	No mapping available
fwVersion	No mapping available
swVersion	No mapping available
hwVersion	No mapping available

268

269

270

7.3 Resource [memory]

271

272

The Resource [memory] is a read-only Resource that shall map to the Device.DeviceInfo.MemoryStatus object of TR-181 [6] for CPE and Virtual Devices.

273

The information shall be retrieved using the GetParameterValues RPC of TR-069 [4].

274

Attempts to modify the attributes of the memory Resource causes an error code “operation unsupported” to be returned.

275

Table 7.3-1: Resource [memory]

276

Attribute Name of [memory]	TR-181 Parameter
memAvailable	Device.DeviceInfo.MemoryStatus.Free
memTotal	Device.DeviceInfo.MemoryStatus.Total

277

278

7.4 Resource [battery]

279

280

The Resource [battery] is a read-only Resource that shall map to an instance of Device.DeviceInfo.X_oneM2M_org_BatteryStatus.Battery.{i} object for CPE and Virtual Devices.

281

The information shall be retrieved using the GetParameterValues RPC of TR-069 [4].

282

Table 7.4-1: Resource [battery]

Attribute Name of [battery]	TR-181 Parameter
batteryLevel	Device.DeviceInfo.X_oneM2M_org_BatteryStatus.Battery.{i}.Level
batteryStatus	Device.DeviceInfo.X_oneM2M_org_BatteryStatus.Battery.{i}.Status

283

284

7.5 Resource [areaNwkInfo]

285 The Resource [areaNwkInfo] is a multi-instance Resource where each instance of the Resource shall map to an instance
286 of Device.X_oneM2M_org_CSE.{i}.M2MareaNetwork.{i} object.

287 As the Resource [areaNwkInfo] is a multi-instance Resource, the M2MareaNetwork object is a multi-object instance
288 that can be created and deleted.

289 The M2MareaNetwork instance shall be created using the Add Object RPC of TR-069 [4].

290 The M2MareaNetwork instance shall be deleted using the Delete Object RPC of TR-069 [4].

291 The information of an M2MareaNetwork shall be retrieved using the GetParameterValues RPC of TR-069 [4].

292 The information of an M2MareaNetwork shall be modified using the SetParameterValues RPC of TR-069 [4].

293 **Table 7.5-1: Resource [areaNwkInfo]**

Attribute Name of [areaNwkInfo]	X_oneM2M_org Parameter
areaNwkType	Device.X_oneM2M_org_CSE.{i}.M2MareaNetwork.{i}.Type
listOfDevices	Device.X_oneM2M_org_CSE.{i}.M2MareaNetwork.{i}.ListOfDevices

294

295

7.6 Resource [areaNwkDeviceInfo]

296 The Resource [areaNwkDeviceInfo] is a multi-instance Resource where each instance of the Resource shall map to an
297 instance of Device.X_oneM2M_org_CSE.{i}.AreaNetworkDevice.{i} object.

298 As the Resource [areaNwkDeviceInfo] is a multi-instance Resource, the AreaNetworkDevice object is a multi-object
299 instance that can be created and deleted.

300 Instances of the Resource [areaNwkDeviceInfo] are referenced in the listOfDevices attribute of the associated Resource
301 [areaNwkInfo].

302 The M2MareaNetworkDevice instance shall be created using the Add Object RPC of TR-069 [4].

303 The M2MareaNetworkDevice instance shall be deleted using the Delete Object RPC of TR-069 [4].

304 The information of an M2MareaNetworkDevice shall be retrieved using the GetParameterValues RPC of TR-069 [4].

305 The information of an M2MareaNetworkDevice shall be modified using the SetParameterValues RPC of TR-069 [4].

306 **Table 7.6-1: Resource [areaNwkDeviceInfo]**

Attribute Name of [areaNwkDeviceInfo]	X_oneM2M_org Parameter
devId	Device.X_oneM2M_org_CSE.{i}.M2MareaNetworkDevice.{i}.Host
devType	Device.X_oneM2M_org_CSE.{i}.M2MareaNetworkDevice.{i}.Type
areaNwkId	Reference to Device.X_oneM2M_org_CSE.{i}.M2MareaNetworkDevice.{i}.M2Mar eaNetwork
sleepInterval	Device.X_oneM2M_org_CSE.{i}.M2MareaNetworkDevice.{i}.SleepInt erval
sleepDuration	Device.X_oneM2M_org_CSE.{i}.M2MareaNetworkDevice.{i}.SleepDu ration

Attribute Name of [areaNwkDeviceInfo]	X_oneM2M_org Parameter
status	Device.X_oneM2M_org_CSE.{i}.M2MareaNetworkDevice.{i}.Status
listOfNeighbors	Device.X_oneM2M_org_CSE.{i}.M2MareaNetworkDevice.{i}.Neighbors

7.7 Resource [eventLog]

The Resource [eventLog] is a multi-instance Resource where each instance of the Resource shall map to an instance of Device.DeviceInfo.X_oneM2M_org_Diagnostics.EventLog.{i} object.

The EventLog instance shall be created using the Add Object RPC of TR-069 [4].

The EventLog instance shall be deleted using the Delete Object RPC of TR-069 [4].

The information of an EventLog instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

The information of an EventLog instance shall be updated using the SetParameterValues RPC of TR-069 [4].

Table 7.7-1: Resource [eventLog]

Attribute Name of [eventLog]	TR-181 Parameter
logTypeId	Device.DeviceInfo.X_oneM2M_org_Diagnostics.EventLog.{i}.Type
logData	Device.DeviceInfo.X_oneM2M_org_Diagnostics.EventLog.{i}.Data
logActionStatus	Device.DeviceInfo.X_oneM2M_org_Diagnostics.EventLog.{i}.Status
logStart	Set to "True", the Device.DeviceInfo.X_oneM2M_org_Diagnostics.EventLog.{i}.Enable parameter is set to "True".
logStop	Set to "True", the Device.DeviceInfo.X_oneM2M_org_Diagnostics.EventLog.{i}.Enable parameter is set to "False".

7.8 Resource [deviceCapability]

The Resource [deviceCapability] represents a capability of device that can be administratively enabled or disabled. The lists of capabilities that are managed are defined in the enumeration of the capabilityName attribute. The TR-181 [6] data model defines a subset of capabilities listed in the deviceCapability enumeration. The supported device capabilities within TR-181 [6] include:

- LAN Interfaces: USB, Wi-Fi, HomePlug, MoCA, UPA
- Hardware Capabilities: SmartCardReader

The information shall be retrieved using the GetParameterValues RPC of TR-069 [4].

The capabilities shall be enabled and disabled using the SetParameterValues RPC of TR-069 [4].

Table 7.8-1: Resource [capabilityInstance]

Attribute Name of [capabilityInstance]	TR-181 Parameter
capabilityName	This attribute is fixed based on the value of the capabilityName attribute.
Attached	Returns “True”
capabilityActionStatus	Status is defined as: <ul style="list-style-type: none"> • Success if the SetParameterValues RPC indicates that the operation was successful. • Failure if the response to the SetParameterValues RPCs indicates that the operation failed. • In process if the SetParameterValues RPC is initiated but the response to the SetParameterValues RPC has not been received.
currentState	USB: Device.USB.Interface.{i}.Enable Wi-Fi: Device.Wi-Fi.Radio.{i}.Enable HomePlug: Device.HomePlug.Interface.{i}.Enable MoCA: Device.MoCA.Interface.{i}.Enable UPA: Device.UPA.Interface.{i}.Enable SmartCardReader: Device.SmartCardReaders.SmartCardReader.{i}.Enable
enable	USB: Device.USB.Interface.{i}.Enable Wi-Fi: Device.Wi-Fi.Radio.{i}.Enable HomePlug: Device.HomePlug.Interface.{i}.Enable MoCA: Device.MoCA.Interface.{i}.Enable UPA: Device.UPA.Interface.{i}.Enable SmartCardReader: Device.SmartCardReaders.SmartCardReader.{i}.Enable
disable	Same parameter is used to disable a capability as the enable attribute.

329

330 7.9 Resource [firmware]

331 The Resource [firmware] represents a firmware instance and is not considered a TR-069 managed entity within the
332 device until the firmware Resource’s update attribute has been written a value of “True”. When this occurs, the TR-069
333 Download RPC shall be invoked.

334

335 Note: In many instances, the server from which the firmware is downloaded requires authentication in the form of
336 Username and Password credentials. The CSE that executes firmware download shall maintain the mapping of the

337 username and password of the download server needed to download the firmware outside the lifecycle of the specific
 338 firmware.

339 **Table 7.9-1: Resource [firmware]**

Attribute Name of [firmware]	RPC Download Arguments
URL	URL
update	When set to the value of “True” executes the Download operations with a FileType “1 Firmware Upgrade Image” is performed.
	Username: Received from the CSE for the download server where the update is set to “True”.
	Password: Received from the CSE for the download server where the update is set to “True”.
	CommandKey: Automatically set by the CSE where the update is set to “True” in order to correlate the TransferComplete response.
	FileSize: 0 (not used)
	TargetFileName: <empty> (not used)
	DelaySeconds: 0 (immediate)
	SuccessURL: <empty> (not used)
	FailureURL: <empty> (not used)

340

341 7.10 Resource [software]

342 The Resource [software] is a multi-instance Resource where each instance of the Resource maps directly to an instance
 343 of Device.SoftwareModules.DeploymentUnit.{i} object for the deployment aspects (install, uninstall) of the Resource
 344 [software]. The install and uninstall operation of the Resource [software] is performed using a combination of the
 345 ChangeDUState and ChangeDUStateComplete RPCs.

346 Once a Resource [software] has been installed, the Resource shall be mapped to the associated
 347 Device.SoftwareModules.ExecutionUnit.{i} objects in order to activate and deactivate the associated execution unit.

348 The Resource [software] version and name shall be retrieved using the GetParameterValues RPC of TR-069 [4].

349 The activate and deactivate operations of the Resource [software] shall be performed by manipulating the
 350 Device.SoftwareModules.ExecutionUnit.{i}.RequestedState parameter using the SetParameterValues RPC.

351 Note: The Resource [software] provides support for only 1 Execution Unit per Deployment Unit. If a Deployment Unit
 352 is discovered by the M2M Service Layer that contains multiple Execution Units for a Deployment Unit; only 1
 353 Execution Unit is exposed. The selection of which Execution Unit is implementation specific.

354

355 **Table 7.10-1: Resource [software]**

Attribute Name of [software]	Description
version	Device.SoftwareModules.DeploymentUnit.{i}.Version

Attribute Name of [software]	Description
name	Device.SoftwareModules.DeploymentUnit.{i}.Name
URL	Device.SoftwareModules.DeploymentUnit.{i}.URL
install	Use the ChangeDUState:InstallOpStruct
installStatus	<p>Status is defined as:</p> <ul style="list-style-type: none"> •Success if the ChangeDUStateComplete RPC indicates that the operation was successful. •Failure if the response to the ChangeDUState or ChangeDUStateComplete RPCs indicates that the operation failed. •In process if the ChangeDUState RPC is initiated but the ChangeDUStateComplete RPC has not been received.
Activate	The action that activates software previously installed.
Deactivate	The action that deactivates software.
activeStatus	<p>Status is defined as:</p> <ul style="list-style-type: none"> •Success if the SetParameterValues RPC indicates that the operation was successful. •Failure if the response to the SetParameterValues RPCs indicates that the operation failed. •In process if the SetParameterValues RPC is initiated but the response to the SetParameterValues RPC has not been received.

Table 7.10-2: RPC ChangeDUState:InstallOpStruct Arguments

RPC ChangeDUState:InstallOpStruct Argument
URL: URL of the Server that M2M Node uses to download the DU.
Username: Username credential of Server that the CPE uses to download the DU – Supplied by the CSE.
Password: Password credential of Server that the CPE uses to download the DU – Supplied by the CSE.
UUID: Supplied by the CSE and used to correlate the DU for the uninstall operation.
ExecutionEnvRef: <empty> not used

Table 7.10-3: RPC ChangeDUState:UninstallOpStruct Arguments

RPC ChangeDUState:Uninstall OpStruct Argument
UUID: UUID of the DU that was installed – Maintained by

RPC ChangeDUState:Uninstall OpStruct Argument
the CSE.
ExecutionEnvRef: <empty> not used

7.11 Resource [reboot]

The Resource [reboot] maps to either the Reboot RPC or FactoryReset RPC of TR-069 [4].

When the reboot attribute of the Resource [reboot] is set to “True”, the CSE shall execute the Reboot RPC of TR-069[4].

When the factoryReset attribute of Resource [reboot] is set to “True”, the CSE shall execute the FactoryReset RPC of TR-069[4].

Table 7.11-1: Resource [reboot]

Attribute Name of [reboot]	Description
reboot	Executes the Reboot RPC
factoryReset	FactoryReset RPC

Table 7.11-2: RPC Reboot Arguments

RPC Reboot Arguments
CommandKey: Automatically set by the CSE where the reboot is set to “True” in order to correlate the “M-Reboot” Event from the next Inform.

7.12 Resource [cmdhPolicy]

The Resource [cmdhPolicy] represents a set of rules defining which CMDH parameters will be used by default when a request issued by a local originator contains the **ec** (event category) parameter but not all other CMDH parameters, see clause D.12 of TS-0001 [1].

The Resource [cmdhPolicy] is a multi-instance Resource where each instance of the Resource shall map to an instance of Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i} object.

The Policy instance shall be created using the Add Object RPC of TR-069 [4].

The Policy instance shall be deleted using the Delete Object RPC of TR-069 [4].

The information of a Policy instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

The information of a Policy instance shall be updated using the SetParameterValues RPC of TR-069 [4].

Table 7.12-1: Resource [cmdhPolicy]

Attribute Name of [cmdhPolicy]	X_oneM2M_org Parameter
name	Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i}.Name

Attribute Name of [cmdhPolicy]	X_oneM2M_org Parameter
cmdhDefaults	Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i}.DefaultRule
cmdhLimits	Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i}.LimitRules
cmdhNetworkAccessRules	Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i}.NetworkAccessECRules
cmdhBuffer	Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i}.BufferRules

382

383 7.12.1 Resource [activeCmdhPolicy]

384 The Resource [activeCmdhPolicy] provides a link to the currently active set of CMDH policies, see clause D.12.1 of
385 TS-0001 [1].

386 The Resource [activeCmdhPolicy] is mapped to the Enable parameter of the
387 Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i} object.

388 The information of a Policy instance shall be updated using the SetParameterValues RPC of TR-069 [4].

389 **Table 7.12.1-1: Resource [activeCmdhPolicy]**

Attribute Name of [activeCmdhPolicy]	X_oneM2M_org Parameter
cmdhPolicy	Device.X_oneM2M_org_CSE.{i}.CMDH.Policy.{i}.Enable At most one Policy instance shall be enabled at a time. As such the Policy instance that has the Enable parameter with a value of “True” is the active CMDH policy.

390

391

392 7.12.2 Resource [cmdhDefaults]

393 The Resource [cmdhDefaults] defines default CMDH policy values, see clause D.12.2 of TS-0001 [1].

394 The Resource [cmdhDefaults] is a multi-instance Resource where each instance of the Resource shall map to an
395 instance of Device.X_oneM2M_org_CSE.{i}.CMDH.Default.{i} object.

396 The Default instance shall be created using the Add Object RPC of TR-069 [4].

397 The Default instance shall be deleted using the Delete Object RPC of TR-069 [4].

398 The information of a Default instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

399 The information of a Default instance shall be updated using the SetParameterValues RPC of TR-069 [4].

400 **Table 7.12.2-1: Resource [cmdhDefaults]**

Attribute Name of [cmdhDefaults]	X_oneM2M_org Parameter
cmdhDefEcValue	Device.X_oneM2M_org_CSE.{i}.CMDH.Default.{i}.DefaultECRules
cmdhEcDefParamValues	Device.X_oneM2M_org_CSE.{i}.CMDH.Default.{i}.DefaultECParamRules

401

7.12.3 Resource [cmdhDefEcValues]

The Resource [cmdhDefEcValues] represents a value for the **ec** (event category) parameter of an incoming request, see clause D.12.3 of TS-0001 [1].

The Resource [cmdhDefEcValues] is a multi-instance Resource where each instance of the Resource shall map to an instance of Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECRule.{i} object.

The DefaultECRule instance shall be created using the Add Object RPC of TR-069 [4].

The DefaultECRule instance shall be deleted using the Delete Object RPC of TR-069 [4].

The information of a DefaultECRule instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

The information of a DefaultECRule instance shall be updated using the SetParameterValues RPC of TR-069 [4].

Table 7.12.3-1: Resource [cmdhDefEcValues]

Attribute Name of [cmdhDefEcValues]	X_oneM2M_org Parameter
order	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECRule.{i}.Order
defEcValue	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECRule.{i}.EventCategory
requestOrigin	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECRule.{i}.RequestOrigin
requestContext	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECRule.{i}.RequestContext
requestContextNotification	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECRule.{i}.RequestContextNotificationEnable
requestCharacteristics	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECRule.{i}.RequestCharacteristics

7.12.4 Resource [cmdhEcDefParamValues]

The Resource [cmdhEcDefParamValues] represents a specific set of default values for the CMDH related parameters **rqet** (request expiration timestamp), **rset** (result expiration timestamp), **oet** (operational execution time), **rp** (response persistence) and **da** (delivery aggregation) that are applicable for a given **ec** (event category) if these parameters are not specified in the request, see clause D.12.4 of TS-0001 [1].

The Resource [cmdhEcDefParamValues] is a multi-instance Resource where each instance of the Resource shall map to an instance of Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECParmRule.{i} object.

The DefaultECParmRule instance shall be created using the Add Object RPC of TR-069 [4].

The DefaultECParmRule instance shall be deleted using the Delete Object RPC of TR-069 [4].

The information of a DefaultECParmRule instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

The information of a DefaultECParmRule instance shall be updated using the SetParameterValues RPC of TR-069 [4].

Table 7.12.4-1: Resource [cmdhEcDefParamValues]

Attribute Name of [cmdhEcDefParamValues]	X_oneM2M_org Parameter
applicableEventCategory	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECParmRule.{i}.EventCategories
defaultRequestExpTime	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECParmRule.{i}.RequestExpTime
defaultResultExpTime	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECParmRule.{i}.ResultExpTime

Attribute Name of [cmdhEcDefParamValues]	X_oneM2M_org Parameter
defaultOpExecTime	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECParmRule.{i}.OperationExecTime
defaultRespPersistence	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECParmRule.{i}.ResponsePersistence
defaultDelAggregation	Device.X_oneM2M_org_CSE.{i}.CMDH.DefaultECParmRule.{i}.DeliveryAggregation

7.12.5 Resource [cmdhLimits]

The Resource [cmdhLimits] represents limits for CMDH related parameter values, see clause D.12.5 of TS-0001 [1].

The Resource [cmdhLimits] is a multi-instance Resource where each instance of the Resource shall map to an instance of Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i} object.

The Limit instance shall be created using the Add Object RPC of TR-069 [4].

The Limit instance shall be deleted using the Delete Object RPC of TR-069 [4].

The information of a Limit instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

The information of a Limit instance shall be updated using the SetParameterValues RPC of TR-069 [4].

Table 7.12.5-1: Resource [cmdhLimits]

Attribute Name of [cmdhLimits]	X_oneM2M_org Parameter
order	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.Order
requestOrigin	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.RequestOrigin
requestContext	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.RequestContext
requestContextNotification	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.RequestContextNotificationEnable
requestCharacteristics	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.RequestCharacteristics
limitsEventCategory	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.EventCategories
limitsRequestExpTime	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.RequestExpTime
limitsResultExpTime	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.ResultExpTime
limitsOpExecTime	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.OperationExecTime
limitsRespPersistence	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.ResponsePersistence
limitsDelAggregation	Device.X_oneM2M_org_CSE.{i}.CMDH.Limit.{i}.DeliveryAggregation

7.12.6 Resource [cmdhNetworkAccessRules]

The Resource [cmdhNetworkAccessRules] defines the usage of underlying networks for forwarding information to other CSEs during processing of CMDH-related requests in a CSE, see clause D.12.6 of TS-0001 [1].

The Resource [cmdhNetworkAccessRules] is a multi-instance Resource where each instance of the Resource shall map to an instance of Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessECRule.{i} object.

The NetworkAccessECRule instance shall be created using the Add Object RPC of TR-069 [4].

444 The NetworkAccessECRule instance shall be deleted using the Delete Object RPC of TR-069 [4].

445 The information of a NetworkAccessECRule instance shall be retrieved using the GetParameterValues RPC of TR-069

446 [4].

447 The information of a NetworkAccessECRule instance shall be updated using the SetParameterValues RPC of TR-069

448 [4].

449 **Table 7.12.6-1: Resource [cmdhNetworkAccessRules]**

Attribute Name of [cmdhNetworkAccessRules]	X_oneM2M_org Parameter
applicableEventCategories	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessECRule.{i}.EventCategories
cmdhNwAccessRule	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessECRule.{i}.NetworkAccessRules

450

451

452 7.12.7 Resource [cmdhNwAccessRule]

453 The Resource [cmdhNwAccessRule] define limits in usage of specific underlying networks for forwarding information

454 to other CSEs during processing of CMDH-related requests, see clause D.12.7 of TS-0001 [1].

455 The Resource [cmdhNwAccessRule] is a multi-instance Resource where each instance of the Resource shall map to an

456 instance of Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessECRule.{i} object.

457 The NetworkAccessRule instance shall be created using the Add Object RPC of TR-069 [4].

458 The NetworkAccessRule instance shall be deleted using the Delete Object RPC of TR-069 [4].

459 The information of a NetworkAccessRule instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

460 The information of a NetworkAccessRule instance shall be updated using the SetParameterValues RPC of TR-069 [4].

461 **Table 7.12.7-1: Resource [cmdhNwAccessRule]**

Attribute Name of [cmdhNwAccessRule]	X_oneM2M_org Parameter
targetNetwork	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessRule.{i}.TargetNetworks
minReqVolume	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessRule.{i}.MinimumReqVolume
backOffParameters	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessRule.{i}.BackoffTime
	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessRule.{i}.BackoffTimeIncrement
	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessRule.{i}.MaximumBackoffTime
otherConditions	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessRule.{i}.OtherConditions
allowedSchedule	Device.X_oneM2M_org_CSE.{i}.CMDH.NetworkAccessRule.{i}.AllowedSchedule

462

463

464 7.12.8 Resource [cmdhBuffer]

465 The Resource [cmdhBuffer] represents limits in usage of buffers for temporarily storing information that needs to be

466 forwarded to other CSEs during processing of CMDH-related requests in a CSE, see clause D.12.8 of TS-0001 [1].

467 The Resource [cmdhBuffer] is a multi-instance Resource where each instance of the Resource shall map to an instance

468 of Device.X_oneM2M_org_CSE.{i}.CMDH.Buffer.{i} object.

469 The Buffer instance shall be created using the Add Object RPC of TR-069 [4].

470 The Buffer instance shall be deleted using the Delete Object RPC of TR-069 [4].

471 The information of a Buffer instance shall be retrieved using the GetParameterValues RPC of TR-069 [4].

472 The information of a Buffer instance shall be updated using the SetParameterValues RPC of TR-069 [4].

473 **Table 7.12.8-1: Resource [cmdhBuffer]**

Attribute Name of [cmdhBuffer]	X_oneM2M_org Parameter
applicableEventCategory	Device.X_oneM2M_org_CSE.{i}.CMDH.Buffer.{i}.EventCategories
maxBufferSize	Device.X_oneM2M_org_CSE.{i}.CMDH.Buffer.{i}.MaximumBufferSize
storagePriority	Device.X_oneM2M_org_CSE.{i}.CMDH.Buffer.{i}.StoragePriority

474

475 7.13 Resource Type <mgmtCmd>

476 Each mgmtCmd Resource shall map to BBF TR-069 RPC commands based on the value of cmdType.

477 Accordingly, execReqArgs shall contain arguments related to the corresponding BBF TR-069 RPCs. The

478 details about corresponding procedure mapping are described in section 8.2.

479 **Table 7.13-1: Resource Type <mgmtCmd>**

Attribute cmdType of mgmtCmd	Attribute execReqArgs of mgmtCmd
cmdType = RESET	Shall include all arguments related to BBF FactoryReset RPC
cmdType = REBOOT	Shall include all arguments related to BBF Reboot RPC
cmdType = UPLOAD	Shall include all arguments related to BBF Reboot RPC
cmdType = DOWNLOAD	Shall contain all arguments related to BBF Reboot RPC
cmdType = SOFTWAREINSTALL	Shall contain all arguments related to BBF ChangeDUState RPC which shall contain "InstallOpStruct" structure.
cmdType = SOFTWAREUNINSTALL	Shall contain all arguments related to BBF ChangeDUState RPC which shall contain "UninstallOpStruct" structure.

480

481 7.14 Resource Type <execInstance>

482 The <execInstance> resource from TS-0004 [2] shall map to BBF CancelTransfer RPC commands when it is

483 disabled/cancelled using a Update operation or deleted using a Delete operation. The details are described in

484 section 8.2.

485

486

487

8 Mapping of procedures for management

488

489

This clause contains all information on how to map management resource primitives from TS-0004 [2] to the Remote Procedure Calls (RPCs) in TR-069 [4].

490

8.1 Resource Type <mgmtObj> primitive mappings

491

492

This clause contains all information on how to map Resource Type <mgmtObj> primitives from TS-0004 [2] to the Remote Procedure Calls (RPCs) in TR-069 [4].

493

8.1.1 Alias-Based Addressing Mechanism

494

495

496

497

In order to utilize the Alias-Based Addressing Mechanism, the mechanism has to be supported by the ACS and CPE in order to map the M2M Service Layer identifier for the Resource instance to the CPE object instance. If the Alias-Based Addressing Mechanism feature is not supported by either the ACS or CPE, the CSE has to retain the mapping of the these M2M Resource instance identifiers.

498

8.1.2 Create primitive mapping

499

500

The Create Request and Response primitives shall map to the AddObject RPC. The AddObject RPC is defined in TR-069 [4] as a synchronous RPC and returns a successful response or one of the following fault codes in Table 8.1.2-1.

501

Table 8.1.2-1: AddObject Fault Code Mapping

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST
9005	Invalid Parameter name (associated with Set/GetParameterValues, GetParameterNames, Set/GetParameterAttributes, AddObject, and DeleteObject)	STATUS_NOT_IMPLEMENTED

502

503

8.1.2.1 M2M Service Layer Resource Instance Identifier mapping

504

505

When the Resource is a multi-instance Resource, the AddObject RPC should utilize the Alias-Based Addressing Mechanism as defined in Section 3.6.1 of TR-069 [4] in order to use the Resource instance value of the URI.

506 8.1.3 Delete primitive mapping

507 8.1.3.1 Delete primitive mapping for deletion of Object Instances

508 The Delete Request and Response primitives that results in the deletion of a Resource shall map to the DeleteObject
509 RPC. The DeleteObject RPC is defined in TR-069 [4] as a synchronous RPC and returns a successful response or one of
510 the following fault codes in Table 8.1.3.1-1.

511 **Table 8.1.3.1-1: DeleteObject Fault Code Mapping**

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST
9005	Invalid Parameter name (associated with Set/GetParameterValues, GetParameterNames, Set/GetParameterAttributes, AddObject, and DeleteObject)	STATUS_NOT_IMPLEMENTED

512

513 8.1.3.2 Delete primitive mapping for software un-install operation

514 The Delete Request and Response primitives that results in a software un-install operation (e.g., Resource [software])
515 shall use the ChangeDUState mechanism defined in TR-069 [4]. The ChangeDUState mechanism is an asynchronous
516 command that consists of the synchronous ChangeDUState RPC for the un-installation request and the asynchronous
517 ChangeDUStateComplete RPC. The ChangeDUState RPC returns a successful response or one of the following fault
518 codes in Table 8.1.3.2-1. A successful response means that the CPE has accepted the ChangeDUState RPC.

519 **Table 8.1.3.2-1: ChangeDUState Fault Code Mapping**

Fault code	Description	Response Status Code
9000	Method not supported	STATUS_BAD_REQUEST
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST

520

521 Once the CPE has attempted to change the state of the deployment unit, the CPE reports the result of the state change
522 operation using the ChangeDUStateComplete RPC. The ChangeDUStateComplete RPC indicates a successful operation
523 or one of the following fault codes in Table 8.1.3.2-2.

524 **Table 8.1.3.2-2: ChangeDUStateComplete Fault Code Mapping**

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST

Fault code	Description	Response Status Code
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9013	Unsupported protocol for file transfer (associated with Upload, Download, ScheduleDownload, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9015	File transfer failure: unable to contact file server (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9016	File transfer failure: unable to access file (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9017	File transfer failure: unable to complete download (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9018	File transfer failure: file corrupted or otherwise unusable (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9022	Invalid UUID Format (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update, and Uninstall)	STATUS_BAD_REQUEST
9023	Unknown Execution Environment (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install only)	STATUS_BAD_REQUEST
9024	Disabled Execution Environment (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update, and Uninstall)	STATUS_BAD_REQUEST
9025	Deployment Unit to Execution Environment Mismatch (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install and Update)	STATUS_BAD_REQUEST
9026	Duplicate Deployment Unit (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install only)	STATUS_BAD_REQUEST
9027	System Resources Exceeded (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install and Update)	STATUS_BAD_REQUEST
9028	Unknown Deployment Unit (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update and Uninstall)	STATUS_BAD_REQUEST
9029	Invalid Deployment Unit State (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update and Uninstall)	STATUS_BAD_REQUEST

Fault code	Description	Response Status Code
9030	Invalid Deployment Unit Update – Downgrade not permitted (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update only)	STATUS_BAD_REQUEST
9031	Invalid Deployment Unit Update – Version not specified (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update only)	STATUS_BAD_REQUEST
9032	Invalid Deployment Unit Update – Version already exists (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update only)	STATUS_BAD_REQUEST

8.1.4 Update primitive mapping

8.1.4.1 Update primitive mapping for Parameter modifications

The Update Request and Response primitives that modifies the value of Resource attributes shall map to the SetParameterValues RPC. The SetParametersValue RPC is defined in TR-069 [4] as a synchronous RPC and returns a successful response or one of the following fault codes in Table 8.1.4.1-1.

Table 8.1.4.1-1: SetParameterValues Fault Code Mapping

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST
9005	Invalid Parameter name (associated with Set/GetParameterValues, GetParameterNames, Set/GetParameterAttributes, AddObject, and DeleteObject)	STATUS_NOT-IMPLEMENTED
9006	Invalid Parameter type (associated with SetParameterValues)	STATUS_BAD_REQUEST
9007	Invalid Parameter value (associated with SetParameterValues)	STATUS_BAD_REQUEST
9008	Attempt to set a non-writable Parameter (associated with SetParameterValues)	STATUS_BAD_REQUEST

8.1.4.2 Update primitive mapping for upload file transfer operations

The Update Request and Response primitives that results in an upload file transfer operation (e.g., logStop attribute of the Resource [eventLog]) shall use the Upload mechanism defined in TR-069 [4]. The Upload mechanism is an asynchronous command that consists of the synchronous Upload RPC for the Upload and the asynchronous TransferComplete RPC. The Upload RPC returns a successful response or one of the following fault codes in Table 8.1.4.2-1. A successful response means that the CPE has accepted the Upload RPC.

Table 8.1.4.2-1: Upload Fault Code Mapping

Fault code	Description	Response Status Code
------------	-------------	----------------------

Fault code	Description	Response Status Code
9000	Method not supported	STATUS_BAD_REQUEST
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST
9011	Upload failure (associated with Upload, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9013	Unsupported protocol for file transfer (associated with Upload, Download, ScheduleDownload, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST

Once the CPE has attempted to upload the file, the CPE reports the result of the Upload operation using the TransferComplete RPC. The TransferComplete RPC indicates a successful operation or one of the following fault codes in Table 8.1.4.2-2.

Table 8.1.4.2-2: TransferComplete Fault Code Mapping

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9010	File transfer failure (associated with Download, ScheduleDownload, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9011	Upload failure (associated with Upload, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9014	File transfer failure: unable to join multicast group (associated with Download, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9015	File transfer failure: unable to contact file server (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9016	File transfer failure: unable to access file (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST

Fault code	Description	Response Status Code
9017	File transfer failure: unable to complete download (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9018	File transfer failure: file corrupted or otherwise unusable (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9019	File transfer failure: file authentication failure (associated with Download, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9020	File transfer failure: unable to complete download within specified time windows (associated with TransferComplete method).	STATUS_BAD_REQUEST

8.1.4.3 Update primitive mapping for download file transfer operations

The Update Request and Response primitives that results in a download file transfer operation (e.g., update attribute of Resource [firmware]) shall use the Download mechanism defined in TR-069 [4]. The Download mechanism is an asynchronous command that consists of the synchronous Download RPC for the Download and the asynchronous TransferComplete RPC. The Download RPC returns a successful response or one of the following fault codes in Table 8.1.4.3-1. A successful response means that the CPE has accepted the Download RPC.

Table 8.1.4.3-1: Download Fault Code Mapping

Fault code	Description	Response Status Code
9000	Method not supported	STATUS_BAD_REQUEST
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST
9010	File transfer failure (associated with Download, ScheduleDownload, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9013	Unsupported protocol for file transfer (associated with Upload, Download, ScheduleDownload, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST

Once the CPE has attempted to download the file, the CPE reports the result of the download operation using the TransferComplete RPC. The TransferComplete RPC indicates a successful operation or one of the following fault codes in Table 8.1.4.3-2.

Table 8.1.4.3-2: TransferComplete Fault Code Mapping

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9010	File transfer failure (associated with Download, ScheduleDownload, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9011	Upload failure (associated with Upload, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9014	File transfer failure: unable to join multicast group (associated with Download, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9015	File transfer failure: unable to contact file server (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9016	File transfer failure: unable to access file (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9017	File transfer failure: unable to complete download (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9018	File transfer failure: file corrupted or otherwise unusable (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9019	File transfer failure: file authentication failure (associated with Download, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST
9020	File transfer failure: unable to complete download within specified time windows (associated with TransferComplete method).	STATUS_BAD_REQUEST

8.1.4.4 Update primitive mapping for reboot operation

The Update Request and Response primitives that results in a reboot operation (e.g., reboot attribute of Resource [reboot]) shall use the Reboot RPC defined in TR-069 [4]. The Reboot RPC is asynchronous command. The Reboot RPC returns a successful response or one of the following fault codes in Table 8.1.4.4-1.

Table 8.1.4.4-1: Reboot Fault Code Mapping

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST

Fault code	Description	Response Status Code
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST

8.1.4.5 Update primitive mapping for factory reset operation

The Update Request and Response primitives that results in a factory reset operation (e.g., factoryReset attribute of Resource [reboot]) shall use the FactoryReset RPC defined in TR-069 [4]. The FactoryReset RPC is an asynchronous command. The FactoryReset RPC returns a successful response or one of the following fault codes in Table 8.1.4.5-1.

Table 8.1.4.5-1: FactoryReset Fault Code Mapping

Fault code	Description	Response Status Code
9000	Method not supported	STATUS_BAD_REQUEST
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST

8.1.4.6 Update primitive mapping for software install operation

The Update Request and Response primitives that results in a software installation operation (e.g., install attribute of Resource [software]) shall use the ChangeDUState mechanism defined in TR-069 [4]. The ChangeDUState mechanism is an asynchronous command that consists of the synchronous ChangeDUState RPC for the download and the asynchronous ChangeDUStateComplete RPC. The ChangeDUState RPC returns a successful response or one of the following fault codes in Table 8.1.4.6-1. A successful response means that the CPE has accepted the ChangeDUState RPC.

Table 8.1.4.6-1: ChangeDUState Fault Code Mapping

Fault code	Description	Response Status Code
9000	Method not supported	STATUS_BAD_REQUEST
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST

Once the CPE has attempted to change the state of the deployment unit, the CPE reports the result of the state change operation using the ChangeDUStateComplete RPC. The ChangeDUStateComplete RPC indicates a successful operation or one of the following fault codes in Table 8.1.4.6-2.

Table 8.1.4.6-2: ChangeDUStateComplete Fault Code Mapping

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST

Fault code	Description	Response Status Code
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9013	Unsupported protocol for file transfer (associated with Upload, Download, ScheduleDownload, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9015	File transfer failure: unable to contact file server (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9016	File transfer failure: unable to access file (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9017	File transfer failure: unable to complete download (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9018	File transfer failure: file corrupted or otherwise unusable (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_BAD_REQUEST
9022	Invalid UUID Format (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update, and Uninstall)	STATUS_BAD_REQUEST
9023	Unknown Execution Environment (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install only)	STATUS_BAD_REQUEST
9024	Disabled Execution Environment (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update, and Uninstall)	STATUS_BAD_REQUEST
9025	Deployment Unit to Execution Environment Mismatch (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install and Update)	STATUS_BAD_REQUEST
9026	Duplicate Deployment Unit (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install only)	STATUS_BAD_REQUEST
9027	System Resources Exceeded (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install and Update)	STATUS_BAD_REQUEST
9028	Unknown Deployment Unit (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update and Uninstall)	STATUS_BAD_REQUEST
9029	Invalid Deployment Unit State (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update and Uninstall)	STATUS_BAD_REQUEST

Fault code	Description	Response Status Code
9030	Invalid Deployment Unit Update – Downgrade not permitted (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update only)	STATUS_BAD_REQUEST
9031	Invalid Deployment Unit Update – Version not specified (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update only)	STATUS_BAD_REQUEST
9032	Invalid Deployment Unit Update – Version already exists (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update only)	STATUS_BAD_REQUEST

8.1.5 Retrieve primitive mapping

The Retrieve Request and Response primitives shall map to the GetParameterValues RPC. The GetParametersValue RPC is defined in TR-069 [4] as a synchronous RPC and returns a successful response or one of the following fault codes in Table 8.1.5-1.

Table 8.1.5-1: GetParameterValues Fault Code Mapping

Fault code	Description	Response Status Code
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST
9005	Invalid Parameter name (associated with Set/GetParameterValues, GetParameterNames, Set/GetParameterAttributes, AddObject, and DeleteObject)	STATUS_BAD_REQUEST

8.1.6 Notify primitive mapping

The NotifyRequest and Response primitives permit notifications to AE or CSEs that have subscribed to a Resource.

While TR-069 [4] has the capability to notify the subscribed ACS when an object's parameter has been modified, TR-069 [4] does not have the capability for an ACS to be notified if any parameter within the object has been modified unless the ACS individually subscribes to all the parameters of the object.

As such the procedure for mapping the Notify Request and Response primitives for TR-069 [4] is not possible unless the CSE subscribes to receive notification to all the parameters of an Object that are mapped to the Resource's attributes.

Note: In many implementations, subscribing to all the parameters of an Object that are mapped to the Resource can cause performance issues in the CPE as well as the CSE. As such using the attribute based subscription capabilities of TR-069 [4] for subscription of Resources should be avoided when possible.

8.1.6.1 Procedure for subscribed Resource attributes.

When a <subscription> Resource for a <mgmtObj> Resource is Created, Deleted or Updated the CSE shall map to the SetParameterAttributes RPC in the following manner:

- TR-069 [4] provides the capability to subscribe to changes of a specific attribute through the use of the SetParameterAttributes RPC using the “Active” value for the Notification parameter.
- TR-069 [4] provides the capability to un-subscribe to changes of a specific attribute through the use of the SetParameterAttributes RPC using the “None” value for the Notification parameter.

The SetParametersAttributes RPC is defined in TR-069 [4] as a synchronous RPC and returns a successful response or one of the following fault codes in Table 8.1.6.1-1.

Table 8.1.6.1-1: SetParameterAttributes Fault Code Mapping

Fault code	Description	Response Status Code
9000	Method not supported	STATUS_BAD_REQUEST
9001	Request denied (no reason specified)	STATUS_BAD_REQUEST
9002	Internal error	STATUS_BAD_REQUEST
9003	Invalid arguments	STATUS_BAD_REQUEST
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_BAD_REQUEST
9010	File transfer failure (associated with Download, ScheduleDownload, TransferComplete or AutonomousTransferComplete methods).	STATUS_BAD_REQUEST

8.1.6.2 Notification primitive mapping

Notify Request and Response primitives shall map to the TR-069 notification mechanism. CPEs produce notifications for subscribed attributes using the TR-069 Inform method, the Inform method has an argument Event that has as one of the EventCodes with the value “4 VALUE CHANGE” indicating that a subscribed parameter’s value has changed. The parameter(s) that have changed are included ParameterList argument of the Inform method.

The ParameterList argument is list of name-value pairs; the name is parameter name and shall be mapped to the objectPath attribute of the Resource while the value is the most recent value of the parameter.

Note: TR-069 CPEs do not report value changes of parameters that were modified by the ACS.

622

623
624

8.2 <mgmtCmd> and <execInstance> resource primitive mappings

625

8.2.1 Update (Execute) primitive for the <mgmtCmd> resource

626
627

When the Update Request primitive for <mgmtCmd> resource addresses the execEnable attribute of the <mgmtCmd> resource, it effectively triggers an Execute <mgmtCmd> procedure..

628
629
630
631

The Hosting CSE performs command conversion of its <execInstance> sub-resources. The mapping between the <execInstance> attributes and the TR-069 [4] RPC procedures triggered is based on the value of the cmdType attribute of the <mgmtCmd> resource defined in Table 8.2.1-1. The CPE acceptance of the corresponding RPC procedures is indicated by returning a successful Response primitive to the initial Update Request.

632
633

The Fault Codes which may be returned by the CPE to the Hosting CSE are mapped onto execStatus codes and stored in the corresponding <execInstance> attributes, and are detailed in the following sub-sections

634

Table 8.2.1-1 Mapping of Execute <mgmtCmd> primitives to BBF TR-069 RPC

cmdType value	BBF TR-069 RPCs
“DOWNLOAD”	Download RPC (see section 8.2.1.1) and TransferComplete RPC (section 8.2.1.3)
“UPLOAD”	Upload RPC (section 8.2.1.2) and TransferComplete RPC (section 8.2.1.3)
“SOFTWAREINSTALL”	ChangeDUState RPC (section 8.2.1.4) and ChangeDUStateComplete RPC (section 8.2.1.5)
“SOFTWAREUNINSTALL”	ChangeDUState RPC (section 8.2.1.4) and ChangeDUStateComplete RPC (section 8.2.1.5)
“REBOOT”	Reboot RPC (section 8.2.1.6)
“RESET”	Factory reset RPC (section 8.2.1.7)

635

636

8.2.1.1 Execute File Download

637
638
639
640

The download file transfer operation may use the Download mechanism defined in TR-069 [4]. The Download mechanism is an asynchronous command which returns a successful response or one of the following fault codes mapped onto execStatus values as detailed in Table 8.2.1.1-1. A successful response to the Update primitive triggering the Execute procedure means that the CPE has accepted the Download RPC.

641

Table 8.2.1.1-1: Download Fault Code Mapping

Fault code	Description	execStatus Code
9000	Method not supported	STATUS_REQUEST_UNSUPPORTED
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9002	Internal error	STATUS_INTERNAL_ERROR
9003	Invalid arguments	STATUS_INVALID_ARGUMENTS

Fault code	Description	execStatus Code
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_RESOURCES_EXCEEDED
9010	File transfer failure (associated with Download, ScheduleDownload, TransferComplete or AutonomousTransferComplete methods).	STATUS_FILE_TRANSFER_FAILED
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods, not associated with Scheduled Download method).	STATUS_FILE_TRANSFER_SERVER_AUTHENTICATION_FAILURE
9013	Unsupported protocol for file transfer (associated with Upload, Download, ScheduleDownload, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_UNSUPPORTED_PROTOCOL

642

643

8.2.1.2 Execute File Upload Operations

644

645

646

647

648

The upload file transfer operation shall use the Upload mechanism defined in TR-069 [4]. The Upload mechanism is an asynchronous command that consists of the synchronous Upload RPC for the Upload and the asynchronous TransferComplete RPC. The Upload RPC returns a successful response or one of the following fault codes mapped onto execStatus values as detailed in Table 8.2.1.2-1. A successful response to the Update primitive triggering the execute procedure means that the CPE has accepted the Upload RPC in Table 8.2.1.2-1.

649

Table 8.2.1.2-1: Upload Fault Code Mapping

Fault code	Description	execStatus Code
9000	Method not supported	STATUS_REQUEST_UNSUPPORTED
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9002	Internal error	STATUS_INTERNAL_ERROR
9003	Invalid arguments	STATUS_INVALID_ARGUMENTS
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_RESOURCES_EXCEEDED
9011	Upload failure (associated with Upload, TransferComplete or AutonomousTransferComplete methods).	STATUS_UPLOAD_FAILED

Fault code	Description	execStatus Code
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_SERVER_AUTHENTICATION_FAILURE
9013	Unsupported protocol for file transfer (associated with Upload, Download, ScheduleDownload, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_UNSUPPORTED_PROTOCOL

8.2.1.3 Report Results using TransferComplete RPC

After a File Download or Upload has been attempted, the result of the operation is reported using the TransferComplete RPC. The TransferComplete RPC indicates a successful operation or one of the following fault codes mapped onto execStatus values in Table 8.2.1.3-2.

Table 8.2.1.3-2: TransferComplete Fault Code Mapping

Fault code	Description	execStatus Code
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9002	Internal error	STATUS_INTERNAL_ERROR
9010	File transfer failure (associated with Download, ScheduleDownload, TransferComplete or AutonomousTransferComplete methods).	STATUS_FILE_TRANSFER_FAILED
9011	Upload failure (associated with Upload, TransferComplete or AutonomousTransferComplete methods).	STATUS_UPLOAD_FAILED
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_SERVER_AUTHENTICATION_FAILURE
9014	File transfer failure: unable to join multicast group (associated with Download, TransferComplete or AutonomousTransferComplete methods).	STATUS_FILE_TRANSFER_FAILED_MULTICAST_GROUP_UNABLE_JOIN
9015	File transfer failure: unable to contact file server (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_SERVER_CONTACT_FAILED
9016	File transfer failure: unable to access file (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_FILE_ACCESS_FAILED

Fault code	Description	execStatus Code
9017	File transfer failure: unable to complete download (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_DOWNLOAD_INCOMPLETE
9018	File transfer failure: file corrupted or otherwise unusable (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_FILE_CORRUPTED
9019	File transfer failure: file authentication failure (associated with Download, TransferComplete or AutonomousTransferComplete methods).	STATUS_FILE_TRANSFER_FILE_AUTHENTICATION_FAILURE
9020	File transfer failure: unable to complete download within specified time windows (associated with TransferComplete method).	STATUS_FILE_TRANSFER_WINDOW_EXCEEDED

8.2.1.4 Execute Software Operations with ChangeDUState RPC

The software installation and uninstall operations shall use the ChangeDUState mechanism defined in TR-069 [4]. The ChangeDUState mechanism is an asynchronous command that consists of the synchronous ChangeDUState RPC and returns a successful response or one of the fault codes mapped onto execStatus values as detailed in Table 8.2.1.4.-1. A successful response to the Update primitive triggering the Execute procedure means that the CPE has accepted the ChangeDUState RPC.

Table 8.2.1.4-1: ChangeDUState Fault Code Mapping

Fault code	Description	execStatus Code
9000	Method not supported	STATUS_REQUEST_UNSUPPORTED
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9002	Internal error	STATUS_INTERNAL_ERROR
9004	Resources exceeded (when used in association with SetParameterValues, this cannot be used to indicate Parameters in error)	STATUS_RESOURCES_EXCEEDED

8.2.1.5 Report Results with ChangeDUStateComplete RPC

After software installation and uninstall operations using a ChangeDUState mechanism as defined in TR-069 [4], the result of the state change operation is retrieved using the ChangeDUStateComplete RPC. The ChangeDUStateComplete RPC indicates a successful operation or one of the fault codes mapped onto execStatus values as detailed in Table 8.2.1.5.-1.

Table 8.2.1.5-1: ChangeDUStateComplete Fault Code Mapping

Fault code	Description	execStatus Code
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED

Fault code	Description	execStatus Code
9003	Invalid arguments	STATUS_INVALID_ARGUMENTS
9012	File transfer server authentication failure (associated with Upload, Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_SERVER_AUTHENTICATION_FAILURE
9013	Unsupported protocol for file transfer (associated with Upload, Download, ScheduleDownload, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_UNSUPPORTED_PROTOCOL
9015	File transfer failure: unable to contact file server (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_SERVER_CONTACT_FAILED
9016	File transfer failure: unable to access file (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_FILE_ACCESS_FAILED
9017	File transfer failure: unable to complete download (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_DOWNLOAD_INCOMPLETE
9018	File transfer failure: file corrupted or otherwise unusable (associated with Download, TransferComplete, AutonomousTransferComplete, DUStateChangeComplete, or AutonomousDUStateChangeComplete methods).	STATUS_FILE_TRANSFER_FAILED_FILE_CORRUPTED
9022	Invalid UUID Format (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update, and Uninstall)	STATUS_INVALID_UUID_FORMAT
9023	Unknown Execution Environment (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install only)	STATUS_UNKNOWN_EXECUTION_ENVIRONMENT
9024	Disabled Execution Environment (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install, Update, and Uninstall)	STATUS_DISABLED_EXECUTION_ENVIRONMENT
9025	Deployment Unit to Execution Environment Mismatch (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install and Update)	STATUS_EXECUTION_ENVIRONMENT_MISMATCH
9026	Duplicate Deployment Unit (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install only)	STATUS_DUPLICATE_DEPLOYMENT_UNIT
9027	System Resources Exceeded (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Install and Update)	STATUS_SYSTEM_RESOURCES_EXCEEDED
9028	Unknown Deployment Unit (associated with DUStateChangeComplete or AutonomousDUStateChangeComplete methods: Update and Uninstall)	STATUS_UNKNOWN_DEPLOYMENT_UNIT

Fault code	Description	execStatus Code
9029	Invalid Deployment Unit State (associated with DUSetChangeComplete or AutonomousDUSetChangeComplete methods: Install, Update and Uninstall)	STATUS_INVALID_DEPLOYMENT_UNIT_STATE
9030	Invalid Deployment Unit Update – Downgrade not permitted (associated with DUSetChangeComplete or AutonomousDUSetChangeComplete methods: Update only)	STATUS_INVALID_DEPLOYMENT_UNIT_UPDATE_DOWNGRADE_DISALLOWED
9031	Invalid Deployment Unit Update – Version not specified (associated with DUSetChangeComplete or AutonomousDUSetChangeComplete methods: Update only)	STATUS_INVALID_DEPLOYMENT_UNIT_UPDATE_UPGRADE_DISALLOWED
9032	Invalid Deployment Unit Update – Version already exists (associated with DUSetChangeComplete or AutonomousDUSetChangeComplete methods: Update only)	STATUS_INVALID_DEPLOYMENT_UNIT_UPDATE_VERSION_EXISTS

8.2.1.6 Execute Reboot operation

The reboot operation shall use the Reboot RPC defined in TR-069 [4]. The Reboot RPC is a synchronous command. A successful response to the Update primitive triggering the Execute procedure means that the CPE has accepted the Reboot RPC. The Reboot RPC returns a successful response or one of the fault codes mapped onto execStatus values as detailed in Table 8.2.1.6-1.

Table 8.2.1.6-1: Reboot Fault Code Mapping

Fault code	Description	execStatus Code
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9002	Internal error	STATUS_INTERNAL_ERROR
9003	Invalid arguments	STATUS_INVALID_ARGUMENTS

8.2.1.7 Execute Factory Reset operation

The factory reset operation shall use the FactoryReset RPC defined in TR-069 [4]. The FactoryReset RPC is a synchronous command. A successful response to the Update primitive triggering the Execute procedure means that the CPE has accepted the FactoryReset RPC. The FactoryReset RPC returns a successful response or one of the fault codes mapped onto execStatus values as detailed in Table 8.2.1.7-1.

Table 8.2.1.7-1: FactoryReset Fault Code Mapping

Fault code	Description	execStatus Code
9000	Method not supported	STATUS_REQUEST_UNSUPPORTED
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9002	Internal error	STATUS_INTERNAL_ERROR

Fault code	Description	execStatus Code
9003	Invalid arguments	STATUS_INVALID_ARGUMENTS

8.2.2 Delete <mgmtCmd> resource primitive mapping

The Delete Request primitive for the <mgmtCmd> resource may initiate TR-069 [4] RPC commands for the corresponding <execInstance> sub-resources as follows:

- If there are no <execInstance> sub-resources with RUNNING execStatus, a successful response to the Delete primitive is returned and the <mgmtCmd> resource is deleted without triggering any TR-069 [4] RPCs.
- If there are <execInstance> sub-resources with RUNNING execStatus that resulted in cancellable TR-069 [4] RPCs (e.g. File Upload and File Download RPCs), a TR-069[4] CancelTransfer RPC shall be initiated for each cancellable operation. Upon completion of all the cancellation operations, if any fault codes are returned by the CPE, an unsuccessful Response to the Delete primitive with status code “Delete mgmtCmd- execInstance cancellation error” is returned, and the <mgmtCmd> resource is not deleted. The execStatus attribute of each specific <execInstance> is set to CANCELLED for successful RPCs or is determined from the RPC fault codes as detailed in Table 8.2.2-1. If all cancellation operations are successful on the managed entity, a successful Response to the Delete primitive is returned and the <mgmtCmd> resource is deleted.
- If there is at least one <execInstance> sub-resource with RUNNING execStatus that resulted in non-cancellable TR-069 [4] RPCs (e.g. RPCs other than File Upload and File Download RPCs), the execStatus attribute of the specific <execInstance> is changed to STATUS_NON_CANCELLABLE. An unsuccessful Response to the Delete primitive with status code “Delete mgmtCmd- execInstance cancellation error” is returned and the <mgmtCmd> resource is not deleted.

Table 8.2.2-1: CancelTransfer Fault Code Mapping for Delete <mgmtCmd>

Fault code	Description	Response Status Code
9000	Method not supported	STATUS_REQUEST_UNSUPPORTED
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9021	Cancellation of file transfer not permitted in current transfer state	STATUS_CANCELLATION_DENIED

8.2.3 Update (Cancel) <execInstance> primitive mapping

When the Update Request primitive for an <execInstance> sub-resource addresses the execDisable attribute of the <execInstance> sub-resource, it effectively triggers a Cancel <execInstance> resource procedure.

The hosting CSE determines whether the <execInstance> resource has a RUNNING execStatus and whether the resulting TR-069 [4] RPCs are cancellable. Currently, only the TR-069 File Upload and File Download RPCs are cancellable using the TR-069 [4] CancelTransfer RPC.

- If the addressed <execInstance> sub-resource has an execStatus other than RUNNING, an unsuccessful Response to the Update primitive is returned with status code “Cancel execInstance – already complete”.
- If the addressed <execInstance> sub-resources has RUNNING execStatus and resulted in cancellable TR-069 [4] RPCs (e.g. File Upload and File Download RPCs), a BBF TR-069 [4] CancelTransfer RPC shall be initiated. For a successful CancelTransfer RPC the execStatus attribute of the specific <execInstance> is set to CANCELLED and a successful Response is sent to the Update primitive. For an unsuccessful CancelTransfer RPC the execStatus attribute is determined from the RPC fault codes as detailed in Table 8.2.3-1 and an

unsuccessful Response is sent to the Update primitive with status code “Cancel execInstance – cancellation error”.

- If the addressed <execInstance> sub-resources has RUNNING execStatus and resulted non-cancellable TR-069 [4] RPCs (e.g. RPCs other than File Upload and File Download RPCs), the execStatus attribute of the specific <execInstance> is changed to STATUS_NON_CANCELLABLE. An unsuccessful Response is sent to the Update primitive with status code “Cancel execInstance – not cancellable”

Table 8.2.3-1: CancelTransfer Fault Code Mapping for Update (Cancel) <execInstance>

Fault code	Description	execStatus Code
9000	Method not supported	STATUS_REQUEST_UNSUPPORTED
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9021	Cancellation of file transfer not permitted in current transfer state	STATUS_REQUEST_UNSUPPORTED

8.2.4 Delete <execInstance> primitive mapping

The Delete Request primitive for an <execInstance> sub-resource may initiate TR-069 [4] RPC commands for the corresponding <execInstance> sub-resources as follows:

- If the addressed <execInstance> sub-resource has an execStatus other than RUNNING, an successful Response to the Delete primitive is returned and the <execInstance> sub-resource is deleted without triggering any TR-069 [4] RPCs.
- If the addressed <execInstance> sub-resource has RUNNING execStatus and resulted in cancellable TR-069 [4] RPCs (e.g. File Upload and File Download RPCs), a BBF TR-069 [4] CancelTransfer RPC shall be initiated. For a successful CancelTransfer RPC a successful response is sent to the Delete primitive and the <execInstance> sub-resource is deleted. For an unsuccessful CancelTransfer RPC the execStatus attribute is determined from the RPC fault codes as detailed in Table 8.2.4-1 and an unsuccessful Response is sent to the Delete primitive with status code “Delete execInstance – cancellation failed”.
- If the addressed <execInstance> sub-resource has RUNNING execStatus and resulted non-cancellable TR-069 [4] RPCs (e.g. RPCs other than File Upload and File Download RPCs), the execStatus attribute is set to STATUS_NOT_CANCELLABLE and an unsuccessful Response is sent to the Update primitive with status code “Delete execInstance – not cancellable”

Table 8.2.4-1: CancelTransfer Fault Code Mapping for Delete <execInstance>

Fault code	Description	execStatus Code
9000	Method not supported	STATUS_REQUEST_UNSUPPORTED
9001	Request denied (no reason specified)	STATUS_REQUEST_DENIED
9021	Cancellation of file transfer not permitted in current transfer state	STATUS_CANCELLATION_DENIED

751 9 Server Interactions

752 This clause specifies how the IN-CSE interacts with an ACS in order to manage the Resources described in this
753 specification. The IN-CSE interaction with an ACS includes:

- 754 • Establishment of the communication session between the IN-CSE and ACS
- 755 • Processing of requests and notifications between the IN-CSE and the ACS
- 756 • Discovery

757 Note: The Broadband Forum has not defined a protocol specification for the Northbound Interface of an ACS. As such,
758 this document only describes the expectations of this interface in the form of requirements on the ACS.

759 9.1 Communication Session Establishment

760 9.1.1 IN-CSE to ACS Communication Session Establishment

761 When the IN-CSE detects that it has to delegate an interaction with a device resource to an ACS, the IN-CSE
762 establishes a communication session with the ACS. The establishment of a communication session between the IN-CSE
763 and ACS provides security dimensions for Access control, Authentication, Non-repudiation, Data confidentiality,
764 Communication security, Data integrity and Privacy adhering to the following TR-131 [7] Architectural requirement
765 A7.

766 The IN-CSE may establish multiple sessions with an ACS based on the security model utilized between the IN-CSE and
767 the ACS.

768 9.1.2 ACS to IN-CSE Communication Session Establishment

769 When the ACS detects a change to resources it manages that the IN-CSE has expressed interest, the ACS requests the
770 IN-CSE to establish a session if a session doesn't exist for the resource being managed. The establishment of a
771 communication session between the IN-CSE and ACS provides security dimensions for Access control,
772 Authentication, Non-repudiation, Data confidentiality, Communication security, Data integrity and Privacy adhering to
773 the following TR-131 [7] Architectural requirement A7.

774 The ACS may establish multiple sessions with an IN-CSE based on the security model utilized between the IN-CSE and
775 the ACS.

776 While a session between the ACS and IN-CSE is not established, the AS retains any notifications or changes in the
777 resources based on an Event retention policy (i.e., time, number of events).

778 When an ACS to IN-CSE interaction is required and a session does not exist, the ACS requests to initiate a session
779 based on a Session Initiation Policy (i.e., Periodic contact establishment (schedule), upon event detection with
780 timeframe window).

781 9.2.3 ACS and IN-CSE Communication Session Requirements

782 When establishing a session from the ACS to the IN-CSE:

- 783 • If a session doesn't exist between the IN-CSE and ACS, the ACS shall retain any notifications or changes in the
784 resources based on an Event retention policy (i.e., time, number of events).
- 785 • When an ACS to IN-CSE interaction is required and a session does not exist, the ACS shall be capable to initiate
786 a session based on a Session Initiation Policy (i.e., Periodic contact establishment (schedule), upon event
787 detection with timeframe window)

788 9.2 Processing of Requests and Responses

789 9.2.1 Request and Notification Formatting

790 Requests and Notifications mechanisms between the IN-CSE and the DM Server format the XML schema of the CPE
791 methods defined in TR-069 [4] as an ACS would format the CPE methods that it would pass to the CPE. The IN-CSE
792 would then also process the CPE methods as defined in TR-069 [4]. Likewise the ACS would send notifications in the
793 format of the XML schema of the CPE for sending events using the Inform RPC.

794 9.2.2 ACS Request Processing Requirements

795 When receiving requests from the IN-CSE the ACS shall be capable of defining mechanisms to support triggering of
796 immediate operations to device. If the device is not available the ACS returns an appropriate error code.

797 The ACS shall provide capability for the IN-CSE to indicate request policies to include: Retry policy, Request Time
798 out.

799 9.2.3 ACS Notification Processing Requirements

800 When sending notifications to the IN-CSE:

- 801 • The ACS shall be capable of providing a mechanism for the IN-CSE to subscribe to events.
- 802 • The ACS shall be capable of providing a list of events for which the IN-CSE can subscribe.
- 803 • The ACS shall be capable of providing a mechanism for the IN-CSE to unsubscribe from events.
- 804 • The ACS shall be capable of providing an event delivery mechanism.
- 805 • The ACS shall be capable of providing the capability for the IN-CSE to request event filters including: Event
806 Code; Specific parameters changing value; Device; Any combination of the previous criteria.
- 807 • The IN-CSE shall be capable of subscribing to be notified of changes to resources it manages.
- 808 • The ACS shall be capable of notifying the IN-CSE of changes to resources to which the client has subscribed.

809 9.3 Discovery and Synchronization of Resources

810 For devices under management, the IN-CSE may discover resources of interest (metadata and values) within a device
811 using the ACS.

812 For resources of interest, the IN-CSE may also express an interest to be notified of a resource if a resource is changed
813 (added, deleted, updated).

814 The IN-CSE shall be capable to discover and subscribe to changes of resources in order to synchronize the IN-CSE with
815 resources of interest of the ACS.

816 9.4 Access Management

817 Once a request has performed an Access Decision by the IN-CSE to allow the request, the IN-CSE shall select the
818 appropriate ACS along with elements the ACS would need to implement access management within the ACS. These
819 would include the Identity of the subject (oneM2M Originator) of the request which is needed in scenarios where the
820 original issuer of the request is needed to be known – this could be done by correlating principals (e.g., Roles,
821 Accounts) used by the IN-CSE and ACS.

822
823
824
825
826
827
828

829

830
831
832

833

834
835
836
837

9.4.1 Access Management Requirements

- The ACS shall be capable of providing a mechanism for the IN-CSE to discover the Access Management elements used to authorize and authenticate access to resources controlled by the ACS.
- The IN-CSE shall be capable of correlating Access Management elements provided by the ACS to Access Management elements used by the IN-CSE.
- The IN-CSE shall be capable of providing secured storage of Access Management elements within the IN-CSE.

10 New Management Technology Specific Resources

TR-181 [6] provides a list of management objects that have been standardized by the Broadband Forum and where possible, clause 7 provides a mapping of the Resources to standardized management objects. This clause provides the oneM2M vendor specific extensions to the TR-181 [6] data model as specified in the ts-0006-1-1.xml.

History

Publication history		
V1.0.1	30 Jan 2015	Release 1 - Publication